



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
VOLVO 26606
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (38 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		PCA0094612	PCA0094601	PCA0052353
Sample Date		Client Info		24 May 2024	02 Jan 2024	04 Apr 2023
Machine Age	mls	Client Info		676470	653284	634094
Oil Age	mls	Client Info		23186	19190	22765
Filter Age	mls	Client Info		23186	19190	22765
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	32	38	23
Chromium	ppm	ASTM D5185m	>20	<1	<1	<1
Nickel	ppm	ASTM D5185m	>2	0	0	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>2	1	0	<1
Aluminum	ppm	ASTM D5185m	>25	3	2	2
Lead	ppm	ASTM D5185m	>40	0	0	0
Copper	ppm	ASTM D5185m	>330	23	10	5
Tin	ppm	ASTM D5185m	>15	<1	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	6	5	2
Potassium	ppm	ASTM D5185m	>20	4	4	2
Fuel		WC Method	>6.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.6	0.7	0.6
Nitration	Abs/cm	*ASTM D7624	>20	9.1	9.8	9.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.1	21.3	19.3
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		12	13	13
Boron	ppm	ASTM D5185m	2	2	<1	<1
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	50	62	61	63
Manganese	ppm	ASTM D5185m	0	<1	<1	1
Magnesium	ppm	ASTM D5185m	950	921	933	963
Calcium	ppm	ASTM D5185m	1050	1070	1101	1114
Phosphorus	ppm	ASTM D5185m	995	950	959	1035
Zinc	ppm	ASTM D5185m	1180	1202	1221	1266
Sulfur	ppm	ASTM D5185m	2600	2733	3140	3357
Oxidation	Abs/.1mm	*ASTM D7414	>25	17.6	16.5	16.3
Base Number (BN)	mg KOH/g	ASTM D2896		5.5	6.1	6.1
Visc @ 100°C	cSt	ASTM D445	12.00	11.1	11.2	11.2



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0094612
Lab Number : 06196438
Unique Number : 11058561
Test Package : FLEET

PERDUE FARMS - WASHINGTON
 P.O. BOX 539
 WASHINGTON, IN
 US 47501
 Contact: DEREK RYAN
 derek.ryan@perdue.com
 T: (812)257-3023
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)