



Machine Id
GLENN JONES (S/N 81-D1-1100)
Component
Starboard Main Engine
Fluid
CHEVRON DELO 710 LS (450 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		MW0055820	MW0055877	MW0055860
Sample Date		Client Info		20 May 2024	15 Jan 2024	20 Nov 2023
Machine Age	hrs	Client Info		9545	6691	5363
Oil Age	hrs	Client Info		9545	6691	5363
Filter Age	hrs	Client Info		201	1417	85
Oil Changed		Client Info		Not Changd	N/A	Not Changd
Filter Changed		Client Info		N/A	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>75	8	9	16
Chromium	ppm	ASTM D5185m	>8	<1	<1	2
Nickel	ppm	ASTM D5185m	>2	0	0	<1
Titanium	ppm	ASTM D5185m	>3	0	0	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>15	1	<1	3
Lead	ppm	ASTM D5185m	>18	2	2	7
Copper	ppm	ASTM D5185m	>80	8	7	17
Tin	ppm	ASTM D5185m	>14	4	3	6
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>20	2	2	6
Potassium	ppm	ASTM D5185m	>20	7	1	4
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.3	0.3	0.3
Nitration	Abs/cm	*ASTM D7624	>20	7.7	7.6	7.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	15.4	15.5	15.5
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>75	2	0	<1
Boron	ppm	ASTM D5185m		40	41	53
Barium	ppm	ASTM D5185m		0	0	11
Molybdenum	ppm	ASTM D5185m		44	42	59
Manganese	ppm	ASTM D5185m		<1	0	<1
Magnesium	ppm	ASTM D5185m		31	36	15
Calcium	ppm	ASTM D5185m		3331	3368	4537
Phosphorus	ppm	ASTM D5185m		22	19	33
Zinc	ppm	ASTM D5185m		22	16	7
Sulfur	ppm	ASTM D5185m		2431	2300	3597
Oxidation	Abs/.1mm	*ASTM D7414	>25	8.6	8.5	8.5
Base Number (BN)	mg KOH/g	ASTM D2896	10.5	6.6	6.8	6.9
Visc @ 100°C	cSt	ASTM D445	15.5	13.5	13.8	13.7


FT-IR (Direct Trend)




Base Number




Viscosity @ 100°C




Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : MW0055820
Lab Number : 06196470
Unique Number : 11058593
Test Package : MAR 2

Received : 31 May 2024
Tested : 02 Jun 2024
Diagnosed : 02 Jun 2024 - Wes Davis

AMERICAN COMMERCIAL LINES
 PO BOX 610, 1701 E. MARKET STREET
 JEFFERSONVILLE, IN
 US 47130
 Contact: RONALD SCHNEIDER
 ronald.schneider@bargeacbl.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
 F: (812)288-1644