



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Area  
**(YA136000)**  
Machine Id  
**3724**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (8 GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0125818</b>	GFL0116389	GFL0098778
Sample Date		Client Info		<b>13 Jun 2024</b>	01 May 2024	29 Dec 2023
Machine Age	hrs	Client Info		<b>10743</b>	10743	10743
Oil Age	hrs	Client Info		<b>10743</b>	10743	10743
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>N/A</b>	N/A	N/A
Filter Changed		Client Info		<b>N/A</b>	N/A	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>75	<b>6</b>	6	3
Chromium	ppm	ASTM D5185m	>5	<b>&lt;1</b>	<1	0
Nickel	ppm	ASTM D5185m	>4	<b>&lt;1</b>	<1	0
Titanium	ppm	ASTM D5185m	>2	<b>&lt;1</b>	<1	0
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>15	<b>2</b>	2	<1
Lead	ppm	ASTM D5185m	>25	<b>&lt;1</b>	1	0
Copper	ppm	ASTM D5185m	>100	<b>&lt;1</b>	<1	0
Tin	ppm	ASTM D5185m	>4	<b>&lt;1</b>	<1	0
Vanadium	ppm	ASTM D5185m		<b>0</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>5</b>	4	8
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	1	0
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>6	<b>0.1</b>	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	<b>4.6</b>	4.4	4.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>16.7</b>	16.6	16.8
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>0</b>	1	<1
Boron	ppm	ASTM D5185m	0	<b>4</b>	12	8
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>57</b>	54	59
Manganese	ppm	ASTM D5185m	0	<b>0</b>	<1	0
Magnesium	ppm	ASTM D5185m	1010	<b>849</b>	817	966
Calcium	ppm	ASTM D5185m	1070	<b>1036</b>	1039	1081
Phosphorus	ppm	ASTM D5185m	1150	<b>883</b>	975	1027
Zinc	ppm	ASTM D5185m	1270	<b>1134</b>	1123	1234
Sulfur	ppm	ASTM D5185m	2060	<b>3145</b>	3256	3201
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>11.8</b>	11.5	12.1
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>8.8</b>	8.8	8.8
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.5</b>	13.3	13.4



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0125818  
**Lab Number** : 06209847  
**Unique Number** : 11082711  
**Test Package** : FLEET

**Received** : 14 Jun 2024  
**Tested** : 15 Jun 2024  
**Diagnosed** : 15 Jun 2024 - Wes Davis

**GFL Environmental - 19DR - Deep Run/TriEast**  
 2287 Leslie R Stroud Road  
 Kinston, NC  
 US 28504-9477  
 Contact: Spencer Ligon  
 spencer.ligon@gflenv.com  
 T: (800)207-6618  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)