



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
I4617
 Component
Diesel Engine
 Fluid
MOBIL DELVAC 1300 SUPER 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		IL0036155	IL0024639	IL0024676
Sample Date		Client Info		11 May 2024	02 Jun 2023	23 Dec 2022
Machine Age	mls	Client Info		226823	0	147118
Oil Age	mls	Client Info		13555	0	0
Filter Age	mls	Client Info		13555	0	0
Oil Changed		Client Info		Changed	N/A	N/A
Filter Changed		Client Info		Changed	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	16	72	98
Chromium	ppm	ASTM D5185m	>20	<1	5	13
Nickel	ppm	ASTM D5185m	>4	<1	<1	0
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	11	51	37
Lead	ppm	ASTM D5185m	>40	0	0	0
Copper	ppm	ASTM D5185m	>330	<1	3	3
Tin	ppm	ASTM D5185m	>15	<1	<1	0
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	6	6	9
Potassium	ppm	ASTM D5185m	>20	13	71	52
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.3	0.9	0.7
Nitration	Abs/cm	*ASTM D7624	>20	11.0	14.0	11.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	20.6	27.5	21.9
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		2	4	1
Boron	ppm	ASTM D5185m	0	72	20	52
Barium	ppm	ASTM D5185m	0	0	0	1
Molybdenum	ppm	ASTM D5185m	0	125	65	73
Manganese	ppm	ASTM D5185m		0	2	2
Magnesium	ppm	ASTM D5185m	0	698	944	829
Calcium	ppm	ASTM D5185m		1317	1644	1301
Phosphorus	ppm	ASTM D5185m		713	1049	1049
Zinc	ppm	ASTM D5185m		944	1339	1261
Sulfur	ppm	ASTM D5185m		3374	3449	2972
Oxidation	Abs/.1mm	*ASTM D7414	>25	19.3	28.6	18.7
Base Number (BN)	mg KOH/g	ASTM D2896	9.4	5.8	6.1	7.7
Visc @ 100°C	cSt	ASTM D445	14	13.0	13.5	12.8



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : IL0036155
Lab Number : 06209898
Unique Number : 11082762
Test Package : FLEET

Received : 14 Jun 2024
Tested : 17 Jun 2024
Diagnosed : 17 Jun 2024 - Wes Davis

RUSH TRUCK LEASING - BOISE IDEALEASE
 770 WEST AMITY ROAD
 BOISE, ID
 US 83705

Contact: MATT BORCHARDT
 borchardtm@rushenterprises.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
 F: (208)639-4859