



Area
G.LOPES CONSTRUCTION INC./Off-Road
Machine Id
L00
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

RECOMMENDATION

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		PCA0122955	PCA0122683	PCA0109859
Sample Date		Client Info		12 Jun 2024	17 Apr 2024	20 Dec 2023
Machine Age	hrs	Client Info		34603	34603	34603
Oil Age	hrs	Client Info		34603	34603	34603
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				ABNORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	17	23	17
Chromium	ppm	ASTM D5185m	>20	<1	<1	<1
Nickel	ppm	ASTM D5185m	>2	1	0	<1
Titanium	ppm	ASTM D5185m	>2	<1	<1	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>25	3	1	1
Lead	ppm	ASTM D5185m	>40	13	21	23
Copper	ppm	ASTM D5185m	>330	12	23	12
Tin	ppm	ASTM D5185m	>15	<1	1	<1
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION













Elemental level of silicon (Si) above normal.

Silicon	ppm	ASTM D5185m	>25	▲ 31	3	3
Potassium	ppm	ASTM D5185m	>20	5	0	0
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.5	0.7	0.6
Nitration	Abs/cm	*ASTM D7624	>20	6.7	8.1	7.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.7	21.0	20.7
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		6	1	0
Boron	ppm	ASTM D5185m	0	4	<1	9
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	59	58	58
Manganese	ppm	ASTM D5185m	0	<1	<1	0
Magnesium	ppm	ASTM D5185m	1010	961	925	936
Calcium	ppm	ASTM D5185m	1070	1134	1104	1011
Phosphorus	ppm	ASTM D5185m	1150	1048	1005	1051
Zinc	ppm	ASTM D5185m	1270	1276	1108	1235
Sulfur	ppm	ASTM D5185m	2060	3138	3424	2976
Oxidation	Abs/.1mm	*ASTM D7414	>25	15.0	16.3	16.7
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	8.61	9.89	10.44
Visc @ 100°C	cSt	ASTM D445	15.4	13.5	13.2	13.1



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
 Sample No. : PCA0122955
 Lab Number : 06210359
 Unique Number : 11083223
 Test Package : MOB 2
 Received : 14 Jun 2024
 Tested : 17 Jun 2024
 Diagnosed : 18 Jun 2024 - Don Baldrige

G LOPES CONSTRUCTION
 565 WINTHROP ST
 TAUNTON, MA
 US 02780
 Contact: BUTCH MCGRATH
 bmcgrath@glopes.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: