



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
Store 4 - Fairmont [RO# 151853]
Machine Id
JOHN DEERE 210G 1FF210GXJNF530240
Component
Swing Drive
Fluid
JOHN DEERE HY-GARD HYD/TRANS (2 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LEC0048441	LEC0047356	LEC0044116
Sample Date		Client Info		10 Jun 2024	11 Jan 2024	28 Aug 2023
Machine Age	hrs	Client Info		2170	1638	1127
Oil Age	hrs	Client Info		1043	511	1127
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Not Changd	Changed
Filter Changed		Client Info		N/A	None	None
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184		49	53	58
Iron	ppm	ASTM D5185m	>151	76	71	114
Chromium	ppm	ASTM D5185m	>11	2	1	3
Nickel	ppm	ASTM D5185m	>10	<1	0	0
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>21	1	<1	2
Lead	ppm	ASTM D5185m	>51	0	<1	0
Copper	ppm	ASTM D5185m	>51	<1	<1	<1
Tin	ppm	ASTM D5185m	>10	0	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>31	14	12	18
Potassium	ppm	ASTM D5185m	>20	2	<1	<1
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	2	<1	2
Boron	ppm	ASTM D5185m	6	31	35	83
Barium	ppm	ASTM D5185m	0	1	<1	0
Molybdenum	ppm	ASTM D5185m	0	6	4	<1
Manganese	ppm	ASTM D5185m		2	1	4
Magnesium	ppm	ASTM D5185m	145	107	92	0
Calcium	ppm	ASTM D5185m	3570	2694	2532	48
Phosphorus	ppm	ASTM D5185m	1290	938	930	541
Zinc	ppm	ASTM D5185m	1640	1001	949	0
Sulfur	ppm	ASTM D5185m		6855	6485	19350
Visc @ 40°C	cSt	ASTM D445	57.0	71.0	74.2	185



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LEC0048441 **Received** : 17 Jun 2024
Lab Number : 06212008 **Tested** : 18 Jun 2024
Unique Number : 11084872 **Diagnosed** : 18 Jun 2024 - Wes Davis
Test Package : CONST (Additional Tests: PQ)

LESLIE EQUIPMENT COMPANY
 105 TENNIS CENTER DR.
 MARIETTA, OH
 US 45750-9765
 Contact: LEANNE KENDALL
 KendalLeanne@lec1.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (740)373-5570