



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Area  
**SUSAN JOHNSON**  
Machine Id  
[**SUSAN JOHNSON**] 005 569359-5  
Component  
Center Reduction Gear  
Fluid  
**CHEVRON MEROPA 320 (100 GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>MW0064812</b>	MW0064769	MW0058684
Sample Date		Client Info		<b>01 Jun 2024</b>	01 May 2024	01 Dec 2023
Machine Age	hrs	Client Info		<b>45280</b>	44566	43985
Oil Age	hrs	Client Info		<b>45280</b>	44566	43985
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Not Changd</b>	Not Changd	Not Changd
Filter Changed		Client Info		<b>N/A</b>	None	None
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>150	<b>96</b>	95	94
Chromium	ppm	ASTM D5185m	>10	<b>0</b>	<1	<1
Nickel	ppm	ASTM D5185m	>10	<b>1</b>	<1	<1
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	1	<1
Silver	ppm	ASTM D5185m		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>25	<b>51</b>	50	47
Lead	ppm	ASTM D5185m	>100	<b>&lt;1</b>	1	<1
Copper	ppm	ASTM D5185m	>50	<b>6</b>	6	5
Tin	ppm	ASTM D5185m	>10	<b>&lt;1</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>50	<b>14</b>	13	13
Potassium	ppm	ASTM D5185m	>20	<b>5</b>	5	4
Water		WC Method	>0.1	<b>NEG</b>	NEG	NEG
Silt	scalar	*Visual	NONE	<b>LIGHT</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>22</b>	20	20
Boron	ppm	ASTM D5185m	20	<b>5</b>	2	5
Barium	ppm	ASTM D5185m		<b>0</b>	<1	0
Molybdenum	ppm	ASTM D5185m	0	<b>49</b>	43	51
Manganese	ppm	ASTM D5185m		<b>1</b>	<1	1
Magnesium	ppm	ASTM D5185m		<b>2</b>	2	2
Calcium	ppm	ASTM D5185m	25	<b>40</b>	47	41
Phosphorus	ppm	ASTM D5185m	235	<b>247</b>	216	213
Zinc	ppm	ASTM D5185m		<b>14</b>	18	8
Sulfur	ppm	ASTM D5185m		<b>9506</b>	8715	7468
Acid Number (AN)	mg KOH/g	ASTM D8045	0.56	<b>0.97</b>	0.95	1.04
Visc @ 40°C	cSt	ASTM D445	304	<b>348</b>	349	349



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513

**Sample No.** : MW0064812

**Lab Number** : 06212527

**Unique Number** : 11085391

**Test Package** : MAR 2

**Received** : 17 Jun 2024

**Tested** : 19 Jun 2024

**Diagnosed** : 19 Jun 2024 - Angela Borella

**INGRAM BARGE**

900 S 3RD ST

PADUCAH, KY

US 42003

Contact: ANTHONY VAN CURA

anthony.vancura@ingrambarga.com

T: (270)415-4467

F: (615)695-3697

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)