



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
CATERPILLAR LILLIAN LOUISE

Component
Port Main Engine

Fluid
CHEVRON DELO 400 MULTIGRADE 15W40 (62 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		MW0071819	MW0067124	MW0049217
Sample Date		Client Info		28 May 2024	28 Apr 2024	29 Mar 2024
Machine Age	hrs	Client Info		0	48180	47630
Oil Age	hrs	Client Info		500	1500	500
Filter Age	hrs	Client Info		500	500	500
Oil Changed		Client Info		Not Changd	Changed	Not Changd
Filter Changed		Client Info		Not Changd	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>75	15	19	14
Chromium	ppm	ASTM D5185m	>8	<1	<1	<1
Nickel	ppm	ASTM D5185m	>2	<1	0	<1
Titanium	ppm	ASTM D5185m	>3	7	11	10
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>15	3	2	2
Lead	ppm	ASTM D5185m	>18	1	2	4
Copper	ppm	ASTM D5185m	>80	17	12	9
Tin	ppm	ASTM D5185m	>14	<1	0	2
Vanadium	ppm	ASTM D5185m		<1	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>20	5	4	4
Potassium	ppm	ASTM D5185m	>20	3	<1	3
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844		0.3	0.3	0.3
Nitration	Abs/cm	*ASTM D7624	>20	9.4	10.0	9.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.6	21.9	20.5
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>75	2	3	3
Boron	ppm	ASTM D5185m		165	118	113
Barium	ppm	ASTM D5185m		<1	0	0
Molybdenum	ppm	ASTM D5185m		69	45	39
Manganese	ppm	ASTM D5185m		<1	<1	1
Magnesium	ppm	ASTM D5185m		594	606	615
Calcium	ppm	ASTM D5185m		1782	2162	2164
Phosphorus	ppm	ASTM D5185m	1360	816	849	875
Zinc	ppm	ASTM D5185m	1480	901	958	996
Sulfur	ppm	ASTM D5185m		2748	3817	4038
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.9	17.4	15.9
Base Number (BN)	mg KOH/g	ASTM D2896	12.2	7.9	6.7	7.1
Visc @ 100°C	cSt	ASTM D445	15.1	13.9	14.0	14.1


FT-IR (Direct Trend)




Base Number




Viscosity @ 100°C




Acid Number




Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Acid Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : MW0071819

Lab Number : 06212936

Unique Number : 11085800

Test Package : MAR 2 (Additional Tests: TAN Man)

Received : 17 Jun 2024

Tested : 19 Jun 2024

Diagnosed : 19 Jun 2024 - Angela Borella

MAGNOLIA MARINE TRANSPORT

697 HAINING ROAD

VICKSBURG, MS

US 39183

Contact: MMT MAINTENANCE PLANNERS

mmtmaintenanceplanners@ergon.com

T: x:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (601)638-8028