



OIL ANALYSIS REPORT

| | |
|-----------------|---------------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |

Machine Id
ISUZU 77036
 Component
Diesel Engine
 Fluid
DIESEL ENGINE OIL SAE 15W30 (10 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number | | Client Info | | WC0875924 | WC0875796 | WC0787545 |
| Sample Date | | Client Info | | 06 Jun 2024 | 28 Nov 2023 | 16 May 2023 |
| Machine Age | mls | Client Info | | 213945 | 0 | 195172 |
| Oil Age | mls | Client Info | | 0 | 0 | 0 |
| Filter Age | mls | Client Info | | 0 | 0 | 0 |
| Oil Changed | | Client Info | | N/A | N/A | Changed |
| Filter Changed | | Client Info | | N/A | N/A | N/A |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |

WEAR

All component wear rates are normal.

| | | | | | | |
|--------------|--------|-------------|------|--------------|------|------|
| Iron | ppm | ASTM D5185m | >100 | 16 | 12 | 6 |
| Chromium | ppm | ASTM D5185m | >20 | <1 | <1 | 0 |
| Nickel | ppm | ASTM D5185m | >4 | <1 | <1 | 0 |
| Titanium | ppm | ASTM D5185m | | <1 | 0 | 0 |
| Silver | ppm | ASTM D5185m | >3 | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | >20 | 4 | 3 | 0 |
| Lead | ppm | ASTM D5185m | >40 | 2 | 0 | <1 |
| Copper | ppm | ASTM D5185m | >330 | 2 | 0 | <1 |
| Tin | ppm | ASTM D5185m | >15 | <1 | 0 | <1 |
| Vanadium | ppm | ASTM D5185m | | <1 | 0 | 0 |
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |

CONTAMINATION

There is no indication of any contamination in the oil.


| | | | | | | |
|------------------|----------|-------------|-------|----------------|-------|-------|
| Silicon | ppm | ASTM D5185m | >25 | 6 | 4 | 4 |
| Potassium | ppm | ASTM D5185m | >20 | 2 | 3 | 2 |
| Fuel | | WC Method | >5 | <1.0 | <1.0 | <1.0 |
| Water | | WC Method | >0.2 | NEG | NEG | NEG |
| Glycol | | WC Method | | NEG | NEG | NEG |
| Soot % | % | *ASTM D7844 | >3 | 1.6 | 0.2 | 0.6 |
| Nitration | Abs/cm | *ASTM D7624 | >20 | 11.4 | 7.4 | 8.0 |
| Sulfation | Abs/.1mm | *ASTM D7415 | >30 | 24.3 | 19.3 | 19.8 |
| Silt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.2 | NEG | NEG | NEG |

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

| | | | | | | |
|------------------|----------|-------------|------|--------------|------|------|
| Sodium | ppm | ASTM D5185m | >25 | 2 | 1 | 2 |
| Boron | ppm | ASTM D5185m | 250 | 147 | 8 | 1 |
| Barium | ppm | ASTM D5185m | 10 | <1 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185m | 100 | 91 | 74 | 63 |
| Manganese | ppm | ASTM D5185m | | <1 | <1 | <1 |
| Magnesium | ppm | ASTM D5185m | 450 | 502 | 957 | 990 |
| Calcium | ppm | ASTM D5185m | 3000 | 1345 | 1124 | 1153 |
| Phosphorus | ppm | ASTM D5185m | 1150 | 1134 | 1049 | 1053 |
| Zinc | ppm | ASTM D5185m | 1350 | 1277 | 1294 | 1314 |
| Sulfur | ppm | ASTM D5185m | 4250 | 3119 | 3216 | 3888 |
| Oxidation | Abs/.1mm | *ASTM D7414 | >25 | 19.2 | 15.7 | 14.9 |
| Base Number (BN) | mg KOH/g | ASTM D2896 | 8.5 | 7.9 | 9.5 | 10.1 |
| Visc @ 100°C | cSt | ASTM D445 | 10.9 | 13.3 | 12.7 | 12.7 |


FT-IR (Direct Trend)




Base Number




Viscosity @ 100°C




Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0875924
Lab Number : 06212954
Unique Number : 11085818
Test Package : FLEET

SALEM NATIONALEASE CORPORATION
 198 PARK PLAZA DRIVE
 WINSTON SALEM, NC
 US 27105
 Contact: Audrey Hopkins
 Audrey.Hopkins@salemcorp.com
 T: (336)767-9642
 F: x:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)