



WEAR CHECK

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area

RTS
Machine Id
[RTS] 887

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (24 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0901448	WC0901462	WC0843766
Sample Date		Client Info		12 Jun 2024	14 Mar 2024	02 Jan 2024
Machine Age	mls	Client Info		503384	492262	481596
Oil Age	mls	Client Info		11122	10666	10746
Filter Age	mls	Client Info		11122	10666	10746
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>75	23	17	16
Chromium	ppm	ASTM D5185m	>5	1	<1	<1
Nickel	ppm	ASTM D5185m	>4	<1	0	0
Titanium	ppm	ASTM D5185m	>2	<1	0	0
Silver	ppm	ASTM D5185m	>2	<1	0	0
Aluminum	ppm	ASTM D5185m	>15	2	2	2
Lead	ppm	ASTM D5185m	>25	2	<1	1
Copper	ppm	ASTM D5185m	>100	1	<1	<1
Tin	ppm	ASTM D5185m	>4	<1	<1	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	6	4	4
Potassium	ppm	ASTM D5185m	>20	33	20	21
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>6	0.3	0.2	0.3
Nitration	Abs/cm	*ASTM D7624	>20	11.5	10.6	10.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.6	21.4	21.6
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		18	11	15
Boron	ppm	ASTM D5185m	0	4	5	9
Barium	ppm	ASTM D5185m	0	<1	0	0
Molybdenum	ppm	ASTM D5185m	60	70	64	62
Manganese	ppm	ASTM D5185m	0	<1	<1	<1
Magnesium	ppm	ASTM D5185m	1010	1014	1015	971
Calcium	ppm	ASTM D5185m	1070	1132	1098	1078
Phosphorus	ppm	ASTM D5185m	1150	1131	1073	1063
Zinc	ppm	ASTM D5185m	1270	1310	1325	1234
Sulfur	ppm	ASTM D5185m	2060	3096	3403	2834
Oxidation	Abs/.1mm	*ASTM D7414	>25	20.8	19.0	19.5
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	7.0	7.1	6.8
Visc @ 100°C	cSt	ASTM D445	15.4	13.5	13.7	12.7



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0901448
Lab Number : 06213029
Unique Number : 11085893
Test Package : FLEET

HUMBOLDT TRANSIT AUTHORITY
 133 V ST
 EUREKA, CA
 US 95501
 Contact: Jim Wilson
 jim@hta.org
 T: (707)443-0828
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)