



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
Store 9 - Marietta
Machine Id
JOHN DEERE 568
Component
Diesel Engine
Fluid
LYDEN 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LEC0051115	LEC0046994	LEC0041243
Sample Date		Client Info		12 Jun 2024	18 Jan 2024	14 Jun 2023
Machine Age	hrs	Client Info		1722	1496	1217
Oil Age	hrs	Client Info		226	279	245
Filter Age	hrs	Client Info		226	279	245
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>51	8	7	9
Chromium	ppm	ASTM D5185m	>11	<1	0	2
Nickel	ppm	ASTM D5185m	>5	<1	0	1
Titanium	ppm	ASTM D5185m		52	64	54
Silver	ppm	ASTM D5185m	>3	0	0	2
Aluminum	ppm	ASTM D5185m	>31	2	1	5
Lead	ppm	ASTM D5185m	>26	<1	<1	5
Copper	ppm	ASTM D5185m	>26	<1	0	2
Tin	ppm	ASTM D5185m	>4	1	<1	2
Vanadium	ppm	ASTM D5185m		<1	<1	2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>120	15	8	10
Potassium	ppm	ASTM D5185m	>20	3	<1	8
Fuel		WC Method	>2.1	<1.0	<1.0	<1.0
Water		WC Method	>0.21	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.2	0.2	0.2
Nitration	Abs/cm	*ASTM D7624	>20	7.6	8.1	8.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.7	18.8	19.5
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.21	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>31	1	2	4
Boron	ppm	ASTM D5185m		95	105	110
Barium	ppm	ASTM D5185m		1	0	18
Molybdenum	ppm	ASTM D5185m		24	12	19
Manganese	ppm	ASTM D5185m		<1	0	2
Magnesium	ppm	ASTM D5185m		391	373	460
Calcium	ppm	ASTM D5185m		1675	1605	1483
Phosphorus	ppm	ASTM D5185m		948	947	913
Zinc	ppm	ASTM D5185m		1149	1111	1099
Sulfur	ppm	ASTM D5185m		3712	3424	3922
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.5	14.5	15.0
Base Number (BN)	mg KOH/g	ASTM D2896		8.1	7.5	8.5
Visc @ 100°C	cSt	ASTM D445		13.3	13.1	13.5



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LEC0051115 **Received** : 18 Jun 2024
Lab Number : 06213111 **Tested** : 19 Jun 2024
Unique Number : 11085975 **Diagnosed** : 20 Jun 2024 - Don Baldrige
Test Package : CONST (Additional Tests: TBN)

LAROCHE TREE SERVICE
 7 COMMERCE PKWY
 BELLAIRE, OH
 US 43906
 Contact: GLEN VARGO
 glen.vargo@larochetree.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)