



OIL ANALYSIS REPORT

| | |
|-----------------|---------------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |

Area
WOOD PROCESSING EQUIPMENT
Machine Id
PLANER STACKER
Component
Hydraulic System
Fluid
SHELL AW HYDRAULIC S2 46 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number | | Client Info | | PE0003595 | PE0000700 | PE06098278 |
| Sample Date | | Client Info | | 07 Jun 2024 | 15 Mar 2024 | 22 Feb 2024 |
| Machine Age | hrs | Client Info | | 0 | 0 | 0 |
| Oil Age | hrs | Client Info | | 0 | 0 | 0 |
| Filter Age | hrs | Client Info | | 0 | 0 | 0 |
| Oil Changed | | Client Info | | N/A | N/A | N/A |
| Filter Changed | | Client Info | | N/A | N/A | N/A |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |

WEAR

All component wear rates are normal.

| PQ | UOM | Method | Limit/Abn | Current | History1 | History2 |
|--------------|--------|-------------|-----------|--------------|----------|----------|
| Iron | ppm | ASTM D5185m | >20 | <1 | 0 | 2 |
| Chromium | ppm | ASTM D5185m | >20 | <1 | <1 | <1 |
| Nickel | ppm | ASTM D5185m | >20 | 0 | 0 | <1 |
| Titanium | ppm | ASTM D5185m | | <1 | <1 | <1 |
| Silver | ppm | ASTM D5185m | | 0 | 0 | <1 |
| Aluminum | ppm | ASTM D5185m | >20 | 2 | 3 | <1 |
| Lead | ppm | ASTM D5185m | >20 | 0 | <1 | <1 |
| Copper | ppm | ASTM D5185m | >20 | <1 | 4 | 2 |
| Tin | ppm | ASTM D5185m | >20 | 0 | <1 | <1 |
| Vanadium | ppm | ASTM D5185m | | 0 | <1 | 0 |
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |

CONTAMINATION











There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

| | | | | | | |
|------------------|--------|--------------|-----------|----------------|----------|----------|
| Silicon | ppm | ASTM D5185m | >15 | 2 | 2 | 2 |
| Potassium | ppm | ASTM D5185m | >20 | 1 | <1 | <1 |
| Water | | WC Method | >0.05 | NEG | NEG | NEG |
| Particles >4µm | | ASTM D7647 | >5000 | 100 | 473 | 196 |
| Particles >6µm | | ASTM D7647 | >1300 | 46 | 59 | 62 |
| Particles >14µm | | ASTM D7647 | >160 | 4 | 5 | 6 |
| Particles >21µm | | ASTM D7647 | >40 | 0 | 2 | 1 |
| Particles >38µm | | ASTM D7647 | >10 | 0 | 0 | 0 |
| Particles >71µm | | ASTM D7647 | >3 | 0 | 0 | 0 |
| Oil Cleanliness | | ISO 4406 (c) | >19/17/14 | 14/13/9 | 16/13/10 | 15/13/10 |
| Silt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.05 | NEG | NEG | NEG |

FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| | | | | | | |
|------------------|----------|-------------|----|-------------|------|------|
| Sodium | ppm | ASTM D5185m | | 7 | 0 | 0 |
| Boron | ppm | ASTM D5185m | | 7 | 0 | 0 |
| Barium | ppm | ASTM D5185m | | 0 | <1 | 5 |
| Molybdenum | ppm | ASTM D5185m | | 0 | <1 | 1 |
| Manganese | ppm | ASTM D5185m | | 0 | 0 | <1 |
| Magnesium | ppm | ASTM D5185m | | 10 | 9 | 7 |
| Calcium | ppm | ASTM D5185m | | 298 | 59 | 51 |
| Phosphorus | ppm | ASTM D5185m | | 378 | 302 | 259 |
| Zinc | ppm | ASTM D5185m | | 456 | 375 | 334 |
| Sulfur | ppm | ASTM D5185m | | 2037 | 2013 | 1811 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | | 0.29 | 0.28 | 0.24 |
| Visc @ 40°C | cSt | ASTM D445 | 46 | 45.8 | 47.8 | 47.0 |



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PE0003595
Lab Number : 06214533
Unique Number : 11087397
Test Package : PLANT (Additional Tests: ICP, KV40, PQ, PrtCount, SCREEN)

WEYERHAEUSER - RAYMOND LUMBER
 1740 51 ELLIS ST
 RAYMOND, WA
 US 98577
 Contact: JOHNNY DOMINGUEZ
 johnny.dominguez@weyerhaeuser.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: