



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
John Deere 300D II 1DW300DXVEE662204
Component
Center Right Final Drive
Fluid
JOHN DEERE GL-5 85W140LS (4 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0216109	LECP0009105	LECP184617
Sample Date		Client Info		17 Jun 2024	26 Nov 2019	04 May 2019
Machine Age	hrs	Client Info		8471	5290	4347
Oil Age	hrs	Client Info		4347	1000	649
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Changed
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184	>1250	29	76	58
Iron	ppm	ASTM D5185m	>750	73	54	94
Chromium	ppm	ASTM D5185m	>9	<1	<1	1
Nickel	ppm	ASTM D5185m	>10	<1	<1	<1
Titanium	ppm	ASTM D5185m		<1	0	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>40	2	1	4
Lead	ppm	ASTM D5185m	>15	0	2	<1
Copper	ppm	ASTM D5185m	>40	6	3	8
Tin	ppm	ASTM D5185m	>10	0	0	0
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	LIGHT
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>75	7	8	11
Potassium	ppm	ASTM D5185m	>20	1	<1	4
Water		WC Method	>0.075	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.075	NEG	NEG	NEG

FLUID CONDITION


The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	5	2	1
Boron	ppm	ASTM D5185m		<1	2	3
Barium	ppm	ASTM D5185m		0	0	<1
Molybdenum	ppm	ASTM D5185m		2	1	3
Manganese	ppm	ASTM D5185m		1	2	2
Magnesium	ppm	ASTM D5185m		2	0	2
Calcium	ppm	ASTM D5185m		110	53	144
Phosphorus	ppm	ASTM D5185m		2327	2623	1725
Zinc	ppm	ASTM D5185m		50	32	61
Sulfur	ppm	ASTM D5185m		31476	10062	21055
Visc @ 40°C	cSt	ASTM D445	350.7	311	343	279


Viscosity @ 40°C




PQ




Ferrous Alloys




PQ



Non-ferrous Metals



Viscosity @ 40°C



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0216109 **Received** : 19 Jun 2024
Lab Number : 06214987 **Tested** : 20 Jun 2024
Unique Number : 11087851 **Diagnosed** : 20 Jun 2024 - Wes Davis
Test Package : CONST (Additional Tests: PQ)

JRE - CHARLOTTE
 9550 STATESVILLE ROAD
 CHARLOTTE, NC
 US 28269
 Contact: CHARLOTTE SHOP
 myoung@jamesriverequipment.com
 T: (704)597-0211
 F: (704)596-6198

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)