



# ASCENDUM

## OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**VOLVO L60H 623293**  
Component  
**Rear Axle**  
Fluid  
**TRANSAXLE OIL SAE 75W80 (--- QTS)**

### RECOMMENDATION

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>ASC0004470</b>	ASC0004472	ASC0006268
Sample Date		Client Info		<b>14 Jun 2024</b>	15 May 2024	28 Mar 2024
Machine Age	hrs	Client Info		<b>2993</b>	2564	0
Oil Age	hrs	Client Info		<b>2993</b>	0	1995
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>N/A</b>	Not Changd	Changed
Filter Changed		Client Info		<b>N/A</b>	N/A	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

### WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>500	<b>52</b>	44	73
Chromium	ppm	ASTM D5185m	>20	<b>1</b>	<1	2
Nickel	ppm	ASTM D5185m	>10	<b>0</b>	0	<1
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	0	<1
Silver	ppm	ASTM D5185m		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>30	<b>2</b>	1	3
Lead	ppm	ASTM D5185m	>50	<b>0</b>	0	0
Copper	ppm	ASTM D5185m	>120	<b>4</b>	4	10
Tin	ppm	ASTM D5185m	>20	<b>0</b>	<1	2
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

### CONTAMINATION





There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>50	<b>14</b>	13	15
Potassium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	0	1
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

### FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		<b>5</b>	2	4
Boron	ppm	ASTM D5185m	160	<b>122</b>	135	119
Barium	ppm	ASTM D5185m	10	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	25	<b>&lt;1</b>	<1	2
Manganese	ppm	ASTM D5185m		<b>2</b>	1	3
Magnesium	ppm	ASTM D5185m	12	<b>18</b>	0	21
Calcium	ppm	ASTM D5185m	3750	<b>3804</b>	3764	3781
Phosphorus	ppm	ASTM D5185m	1200	<b>1224</b>	1286	1240
Zinc	ppm	ASTM D5185m	1500	<b>1484</b>	1541	1530
Sulfur	ppm	ASTM D5185m	6000	<b>4157</b>	4816	4351
Visc @ 40°C	cSt	ASTM D445	48	<b>42.3</b>	44.4	43.4



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : ASC0004470  
**Lab Number** : 06215050  
**Unique Number** : 11087914  
**Test Package** : CONST

**Received** : 19 Jun 2024  
**Tested** : 20 Jun 2024  
**Diagnosed** : 20 Jun 2024 - Wes Davis

**520 - ASCENDUM MACHINERY INC - KNOXVILLE**  
 5730 RUTLEDGE PIKE  
 KNOXVILLE, TN  
 US 37924

Contact: BRANDON GRANT  
 brandon.grant@ascendummachinery.com  
 T: (865)525-1845  
 F: (865)525-0251

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)