



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**913091**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0122391</b>	GFL0117683	GFL0108741
Sample Date		Client Info		<b>12 Jun 2024</b>	12 Apr 2024	20 Mar 2024
Machine Age	hrs	Client Info		<b>4328</b>	3925	3738
Oil Age	hrs	Client Info		<b>3925</b>	2939	3738
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Changed</b>	Changed	Not Changd
Filter Changed		Client Info		<b>Changed</b>	Changed	Not Changd
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>120	<b>5</b>	21	7
Chromium	ppm	ASTM D5185m	>20	<b>0</b>	2	<1
Nickel	ppm	ASTM D5185m	>5	<b>&lt;1</b>	3	<1
Titanium	ppm	ASTM D5185m	>2	<b>0</b>	<1	<1
Silver	ppm	ASTM D5185m	>2	<b>&lt;1</b>	<1	0
Aluminum	ppm	ASTM D5185m	>20	<b>2</b>	2	2
Lead	ppm	ASTM D5185m	>40	<b>0</b>	2	<1
Copper	ppm	ASTM D5185m	>330	<b>&lt;1</b>	6	1
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	2	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>3</b>	5	7
Potassium	ppm	ASTM D5185m	>20	<b>3</b>	2	2
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>4	<b>0.4</b>	0.9	0.1
Nitration	Abs/cm	*ASTM D7624	>20	<b>7.6</b>	10.9	6.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>19.2</b>	23.3	17.9
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>4</b>	4	6
Boron	ppm	ASTM D5185m	0	<b>2</b>	0	<1
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>56</b>	61	59
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	2	0
Magnesium	ppm	ASTM D5185m	1010	<b>970</b>	895	910
Calcium	ppm	ASTM D5185m	1070	<b>1074</b>	1080	1197
Phosphorus	ppm	ASTM D5185m	1150	<b>1042</b>	1007	1014
Zinc	ppm	ASTM D5185m	1270	<b>1286</b>	1193	1232
Sulfur	ppm	ASTM D5185m	2060	<b>3434</b>	2787	3018
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>15.1</b>	19.4	13.8
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>7.6</b>	5.0	8.7
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.2</b>	14.0	14.07



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0122391 **Received** : 20 Jun 2024  
**Lab Number** : 06215352 **Tested** : 21 Jun 2024  
**Unique Number** : 11088216 **Diagnosed** : 21 Jun 2024 - Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 415 - Michigan East**  
 6200 Elmridge  
 Sterling Heights, MI  
 US 48313  
 Contact: Frank Wolak  
 fwolak@gflenv.com  
 T: (586)825-9514  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)