



PacLease

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
8574803
 Component
Diesel Engine
 Fluid
CHEVRON DELO 400 SAE 10W30 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		RPL0019013	RPL0013898	RPL0010363
Sample Date		Client Info		21 May 2024	24 Jan 2024	03 Jul 2023
Machine Age	hrs	Client Info		0	3451	84232
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Changed	Changed
Filter Changed		Client Info		Not Changd	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	19	34	95
Chromium	ppm	ASTM D5185m	>20	1	4	9
Nickel	ppm	ASTM D5185m	>4	<1	2	2
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m	>3	0	<1	0
Aluminum	ppm	ASTM D5185m	>20	8	18	108
Lead	ppm	ASTM D5185m	>40	3	4	9
Copper	ppm	ASTM D5185m	>330	1	3	13
Tin	ppm	ASTM D5185m	>15	1	1	3
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	9	11	24
Potassium	ppm	ASTM D5185m	>20	26	49	317
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.2	0.2	0.4
Nitration	Abs/cm	*ASTM D7624	>20	11.2	10.7	12.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	25.1	24.3	27.4
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		1	0	9
Boron	ppm	ASTM D5185m		21	32	16
Barium	ppm	ASTM D5185m		<1	0	0
Molybdenum	ppm	ASTM D5185m		46	49	14
Manganese	ppm	ASTM D5185m		<1	1	3
Magnesium	ppm	ASTM D5185m		444	491	791
Calcium	ppm	ASTM D5185m		1660	1732	1582
Phosphorus	ppm	ASTM D5185m	1260	676	797	770
Zinc	ppm	ASTM D5185m	1400	901	989	960
Sulfur	ppm	ASTM D5185m		2478	2671	3712
Oxidation	Abs/.1mm	*ASTM D7414	>25	28.0	26.4	24.9
Base Number (BN)	mg KOH/g	ASTM D2896	10.1	6.5	6.3	4.5
Visc @ 100°C	cSt	ASTM D445	11.1	10.9	11.1	11.5



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : RPL0019013
Lab Number : 06215497
Unique Number : 11088361
Test Package : FLEET

Received : 20 Jun 2024
Tested : 21 Jun 2024
Diagnosed : 21 Jun 2024 - Don Baldrige

RTL PACLEASE - 7001 - Houston
 6300 N. Loop East
 Houston, TX
 US 77026
 Contact: RODNEY BRIGGS
 briggs@rushenterprises.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: