



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area  
**TIMOTHY RAINES [SR00100204]**  
 Machine Id  
**VOLVO PENTA 51230135148 - INBOARD**  
 Component  
**Center Gearbox**  
 Fluid  
**CHEVRON AUTOMATIC TRANS FLUID MD-3 (4 QTS)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VPA062986	---	---
Sample Date		Client Info		06 Jun 2024	---	---
Machine Age	hrs	Client Info		31	---	---
Oil Age	hrs	Client Info		31	---	---
Filter Age	hrs	Client Info		0	---	---
Oil Changed		Client Info		Changed	---	---
Filter Changed		Client Info		Changed	---	---
Sample Status				NORMAL	---	---

**WEAR**

All component wear rates are normal.

PQ		ASTM D8184		35	---	---
Iron	ppm	ASTM D5185m	>150	38	---	---
Chromium	ppm	ASTM D5185m	>10	0	---	---
Nickel	ppm	ASTM D5185m	>10	0	---	---
Titanium	ppm	ASTM D5185m		0	---	---
Silver	ppm	ASTM D5185m		0	---	---
Aluminum	ppm	ASTM D5185m	>5	1	---	---
Lead	ppm	ASTM D5185m	>65	3	---	---
Copper	ppm	ASTM D5185m	>80	20	---	---
Tin	ppm	ASTM D5185m	>8	0	---	---
Vanadium	ppm	ASTM D5185m		<1	---	---
White Metal	scalar	*Visual	NONE	NONE	---	---
Yellow Metal	scalar	*Visual	NONE	NONE	---	---

**CONTAMINATION**











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	7	---	---
Potassium	ppm	ASTM D5185m	>20	<1	---	---
Water		WC Method	>0.2	NEG	---	---
Silt	scalar	*Visual	NONE	NONE	---	---
Debris	scalar	*Visual	NONE	NONE	---	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---	---
Appearance	scalar	*Visual	NORML	NORML	---	---
Odor	scalar	*Visual	NORML	NORML	---	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---	---

**FLUID CONDITION**

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		3	---	---
Boron	ppm	ASTM D5185m		51	---	---
Barium	ppm	ASTM D5185m		2	---	---
Molybdenum	ppm	ASTM D5185m		0	---	---
Manganese	ppm	ASTM D5185m		<1	---	---
Magnesium	ppm	ASTM D5185m		49	---	---
Calcium	ppm	ASTM D5185m		12	---	---
Phosphorus	ppm	ASTM D5185m		330	---	---
Zinc	ppm	ASTM D5185m		235	---	---
Sulfur	ppm	ASTM D5185m		5634	---	---
Visc @ 40°C	cSt	ASTM D445	33.6	29.2	---	---



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : VPA062986 **Received** : 20 Jun 2024  
**Lab Number** : 06216061 **Tested** : 22 Jun 2024  
**Unique Number** : 11088925 **Diagnosed** : 23 Jun 2024 - Don Baldrige  
**Test Package** : MOB 1 ( Additional Tests: PQ )

**Pacific Power Group - VP981534**  
 7215 S 228th St  
 Kent, WA  
 US 98032  
 Contact: PAT RYAN  
 pryan@pacificpowergroup.com  
 T: (253)520-5163  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)