



LIEBHERR

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	ATTENTION



Machine Id
LIEBHERR LH110 1227-155752
Component
Swing Drive
Fluid
SAE 30W (--- GAL)

RECOMMENDATION

The oil change at the time of sampling has been noted. Resample at the next service interval to monitor.

WEAR

All component wear rates are normal.

CONTAMINATION

There is no indication of any contamination in the oil.

FLUID CONDITION






Additive levels indicate the addition of a different brand, or type of oil. The condition of the oil is acceptable for the time in service.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LH0267077	LH0267545	LH0280586
Sample Date		Client Info		10 Jun 2024	20 May 2024	18 Apr 2024
Machine Age	hrs	Client Info		2998	2578	1980
Oil Age	hrs	Client Info		967	547	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Not Changd	Changed
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				ATTENTION	ATTENTION	ATTENTION

Iron	ppm	ASTM D5185m	>350	50	36	182
Chromium	ppm	ASTM D5185m	>15	<1	<1	<1
Nickel	ppm	ASTM D5185m	>5	0	<1	0
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m		0	<1	0
Aluminum	ppm	ASTM D5185m	>5	2	2	1
Lead	ppm	ASTM D5185m	>10	0	0	1
Copper	ppm	ASTM D5185m	>300	142	99	116
Tin	ppm	ASTM D5185m	>15	4	2	10
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

Silicon	ppm	ASTM D5185m	>15	3	3	5
Potassium	ppm	ASTM D5185m	>20	1	2	<1
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	MODER
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

Sodium	ppm	ASTM D5185m		<1	4	2
Boron	ppm	ASTM D5185m		9	8	6
Barium	ppm	ASTM D5185m		0	0	3
Molybdenum	ppm	ASTM D5185m		3	4	0
Manganese	ppm	ASTM D5185m		<1	<1	2
Magnesium	ppm	ASTM D5185m		● 37	● 34	● <1
Calcium	ppm	ASTM D5185m		● 324	● 259	● 96
Phosphorus	ppm	ASTM D5185m		● 527	● 440	● 2154
Zinc	ppm	ASTM D5185m		● 196	● 165	● 53
Sulfur	ppm	ASTM D5185m		● 11597	● 11910	● 28687
Visc @ 40°C	cSt	ASTM D445	95.0	94.2	90.2	● 175



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LH0267077
Lab Number : 06216178
Unique Number : 11089042
Test Package : CONST
Received : 20 Jun 2024
Tested : 21 Jun 2024
Diagnosed : 23 Jun 2024 - Don Baldrige

KINDER MORGAN
 4301 IVERSON
 TRINITY, AL
 US 35601

Contact: RICKY JOHNSON
 ricky_johnson@kindermorgan.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
 F: (256)355-5250