



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area

(YA154621)

Machine Id

PETERBILT 2864

Component

Diesel Engine

Fluid

PETRO CANADA DURON SHP 15W40 (10 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0119672	GFL0111363	GFL0072243
Sample Date		Client Info		05 Jun 2024	03 Feb 2024	12 Jul 2023
Machine Age	mls	Client Info		14253	0	193713
Oil Age	mls	Client Info		0	0	11500
Filter Age	mls	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	Changed
Filter Changed		Client Info		N/A	N/A	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

Metal levels are typical for a new component breaking in.

Iron	ppm	ASTM D5185m	>165	8	8	10
Chromium	ppm	ASTM D5185m	>5	<1	<1	<1
Nickel	ppm	ASTM D5185m	>4	0	<1	<1
Titanium	ppm	ASTM D5185m	>2	<1	<1	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>20	2	1	1
Lead	ppm	ASTM D5185m	>150	2	<1	2
Copper	ppm	ASTM D5185m	>90	<1	<1	1
Tin	ppm	ASTM D5185m	>5	0	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>35	5	6	4
Potassium	ppm	ASTM D5185m	>20	2	5	3
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>7.5	0.3	0.1	0.4
Nitration	Abs/cm	*ASTM D7624	>20	7.7	6.4	8.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.0	18.0	19.6
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		13	0	17
Boron	ppm	ASTM D5185m	0	2	3	7
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	62	60	65
Manganese	ppm	ASTM D5185m	0	0	<1	<1
Magnesium	ppm	ASTM D5185m	1010	975	926	899
Calcium	ppm	ASTM D5185m	1070	1098	981	1108
Phosphorus	ppm	ASTM D5185m	1150	1037	927	1016
Zinc	ppm	ASTM D5185m	1270	1306	1188	1196
Sulfur	ppm	ASTM D5185m	2060	2999	2890	3066
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.5	13.9	15.1
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	8.0	8.4	7.9
Visc @ 100°C	cSt	ASTM D445	15.4	12.9	13.0	12.9



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0119672
Lab Number : 06216482
Unique Number : 11089346
Test Package : FLEET

Received : 20 Jun 2024
Tested : 22 Jun 2024
Diagnosed : 22 Jun 2024 - Wes Davis

GFL Environmental - 004 - Newport - Central Coast
 427 Roberts Road
 Newport, NC
 US 28570

Contact: Marquis Williams
 marquis.williams@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
 F: (252)223-6010