



# OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Area  
**Store 4 - Fairmont [RO# 152206]**  
Machine Id  
**JOHN DEERE 160G 1FF160GXLNF058611**  
Component  
**Hydraulic System**  
Fluid  
**HITACHI HYDRAULIC SUPER EX 46HN (56 GAL)**

## RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>LEC0050931</b>	LEC0038764	LEC0030087
Sample Date		Client Info		<b>17 Jun 2024</b>	23 Jan 2023	03 Aug 2022
Machine Age	hrs	Client Info		<b>1435</b>	560	155
Oil Age	hrs	Client Info		<b>1435</b>	560	155
Filter Age	hrs	Client Info		<b>1435</b>	560	155
Oil Changed		Client Info		<b>Not Chngd</b>	Not Chngd	Not Chngd
Filter Changed		Client Info		<b>Not Chngd</b>	Not Chngd	Not Chngd
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

## WEAR

All component wear rates are normal.

PQ		ASTM D8184	>50	<b>17</b>	7	18
Iron	ppm	ASTM D5185m	>32	<b>4</b>	2	1
Chromium	ppm	ASTM D5185m	>9	<b>&lt;1</b>	0	0
Nickel	ppm	ASTM D5185m	>5	<b>&lt;1</b>	0	0
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
Aluminum	ppm	ASTM D5185m	>9	<b>3</b>	<1	0
Lead	ppm	ASTM D5185m	>28	<b>1</b>	0	<1
Copper	ppm	ASTM D5185m	>50	<b>3</b>	3	2
Tin	ppm	ASTM D5185m	>5	<b>&lt;1</b>	0	0
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

## CONTAMINATION











The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

Silicon	ppm	ASTM D5185m	>11	<b>2</b>	<1	<1
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	1	1
Water		WC Method	>0.075	<b>NEG</b>	NEG	NEG
Particles >4µm		ASTM D7647	>80000	<b>1198</b>	571	1195
Particles >6µm		ASTM D7647	>20000	<b>111</b>	92	131
Particles >14µm		ASTM D7647	>640	<b>4</b>	9	13
Particles >21µm		ASTM D7647	>160	<b>1</b>	4	3
Particles >38µm		ASTM D7647	>40	<b>0</b>	0	0
Particles >71µm		ASTM D7647	>10	<b>0</b>	0	0
Oil Cleanliness		ISO 4406 (c)	>23/21/16	<b>17/14/9</b>	16/14/10	17/14/11
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.075	<b>NEG</b>	NEG	NEG

## FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>21	<b>0</b>	0	0
Boron	ppm	ASTM D5185m		<b>4</b>	0	0
Barium	ppm	ASTM D5185m		<b>1</b>	2	0
Molybdenum	ppm	ASTM D5185m		<b>4</b>	0	0
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	<1	0
Magnesium	ppm	ASTM D5185m		<b>10</b>	<1	<1
Calcium	ppm	ASTM D5185m		<b>48</b>	2	1
Phosphorus	ppm	ASTM D5185m	827	<b>558</b>	519	541
Zinc	ppm	ASTM D5185m	0	<b>63</b>	35	31
Sulfur	ppm	ASTM D5185m	13	<b>180</b>	82	124
Acid Number (AN)	mg KOH/g	ASTM D8045	0.06	<b>0.16</b>	0.16	0.10
Visc @ 40°C	cSt	ASTM D445	47	<b>47.6</b>	47.6	47.9



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : LEC0050931 **Received** : 21 Jun 2024  
**Lab Number** : 06216777 **Tested** : 24 Jun 2024  
**Unique Number** : 11089641 **Diagnosed** : 24 Jun 2024 - Wes Davis  
**Test Package** : CONST ( Additional Tests: PQ )

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

**LESLIE EQUIPMENT COMPANY**  
 105 TENNIS CENTER DR.  
 MARIETTA, OH  
 US 45750-9765  
 Contact: LEANNE KENDALL  
 KendalLeanne@lec1.com

T:  
 F: (740)373-5570