



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	ATTENTION



Area
Store 4 - Fairmont
Machine Id
JOHN DEERE 210G 1FF210GXANF530291
Component
Left Propel Gearbox
Fluid
JOHN DEERE GL-5 80W90 (2 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LEC0050066	LEC0041410	---
Sample Date		Client Info		19 Jun 2024	30 May 2023	---
Machine Age	hrs	Client Info		899	479	---
Oil Age	hrs	Client Info		420	479	---
Filter Age	hrs	Client Info		0	0	---
Oil Changed		Client Info		Changed	Changed	---
Filter Changed		Client Info		N/A	None	---
Sample Status				ATTENTION	NORMAL	---

WEAR

All component wear rates are normal.

PQ		ASTM D8184		116	378	---
Iron	ppm	ASTM D5185m	>1250	342	650	---
Chromium	ppm	ASTM D5185m	>10	5	11	---
Nickel	ppm	ASTM D5185m	>10	0	0	---
Titanium	ppm	ASTM D5185m		<1	<1	---
Silver	ppm	ASTM D5185m		0	0	---
Aluminum	ppm	ASTM D5185m		2	<1	---
Lead	ppm	ASTM D5185m		<1	0	---
Copper	ppm	ASTM D5185m		1	2	---
Tin	ppm	ASTM D5185m		0	0	---
Vanadium	ppm	ASTM D5185m		<1	0	---
White Metal	scalar	*Visual	NONE	NONE	MODER	---
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	---

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m		17	25	---
Potassium	ppm	ASTM D5185m	>20	3	3	---
Water		WC Method	>0.2	NEG	NEG	---
Silt	scalar	*Visual	NONE	LIGHT	NONE	---
Debris	scalar	*Visual	NONE	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	---

FLUID CONDITION

The oil viscosity is lower than normal. This plus the additive levels indicates the addition of a different brand, or type of oil. Confirm oil type.

Sodium	ppm	ASTM D5185m		1	<1	---
Boron	ppm	ASTM D5185m		31	72	---
Barium	ppm	ASTM D5185m		3	0	---
Molybdenum	ppm	ASTM D5185m		4	<1	---
Manganese	ppm	ASTM D5185m		5	11	---
Magnesium	ppm	ASTM D5185m		101	0	---
Calcium	ppm	ASTM D5185m		3063	13	---
Phosphorus	ppm	ASTM D5185m		1042	504	---
Zinc	ppm	ASTM D5185m		1094	7	---
Sulfur	ppm	ASTM D5185m		7219	18257	---
Visc @ 40°C	cSt	ASTM D445		72.1	184	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LEC0050066 **Received** : 21 Jun 2024
Lab Number : 06217088 **Tested** : 24 Jun 2024
Unique Number : 11089952 **Diagnosed** : 24 Jun 2024 - Sean Felton
Test Package : CONST (Additional Tests: PQ)

LESLIE EQUIPMENT COMPANY
 105 TENNIS CENTER DR.
 MARIETTA, OH
 US 45750-9765
 Contact: LEANNE KENDALL
 KendalLeanne@lec1.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
 F: (740)373-5570