



# OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id  
**KIOTI CK2620H PA3TA1430**  
 Component  
**Diesel Engine**  
 Fluid  
**SHELL Rotella T5 15W-40 (--- GAL)**

## RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>KT0001387</b>	---	---
Sample Date		Client Info		<b>01 Jun 2024</b>	---	---
Machine Age	hrs	Client Info		<b>79</b>	---	---
Oil Age	hrs	Client Info		<b>20</b>	---	---
Filter Age	hrs	Client Info		<b>20</b>	---	---
Oil Changed		Client Info		<b>Changed</b>	---	---
Filter Changed		Client Info		<b>Changed</b>	---	---
Sample Status				<b>NORMAL</b>	---	---

## WEAR

Metal levels are typical for a new component breaking in.

Iron	ppm	ASTM D5185m	>100	<b>20</b>	---	---
Chromium	ppm	ASTM D5185m	>20	<b>0</b>	---	---
Nickel	ppm	ASTM D5185m	>4	<b>1</b>	---	---
Titanium	ppm	ASTM D5185m		<b>0</b>	---	---
Silver	ppm	ASTM D5185m	>3	<b>0</b>	---	---
Aluminum	ppm	ASTM D5185m	>20	<b>32</b>	---	---
Lead	ppm	ASTM D5185m	>40	<b>8</b>	---	---
Copper	ppm	ASTM D5185m	>330	<b>83</b>	---	---
Tin	ppm	ASTM D5185m	>15	<b>8</b>	---	---
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	---	---
White Metal	scalar	*Visual	NONE	<b>NONE</b>	---	---
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	---	---

## CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>13</b>	---	---
Potassium	ppm	ASTM D5185m	>20	<b>3</b>	---	---
Fuel		WC Method	>5	<b>&lt;1.0</b>	---	---
Water		WC Method	>0.2	<b>NEG</b>	---	---
Glycol		WC Method		<b>NEG</b>	---	---
Soot %	%	*ASTM D7844	>3	<b>0.1</b>	---	---
Nitration	Abs/cm	*ASTM D7624	>20	<b>5.3</b>	---	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>22.6</b>	---	---
Silt	scalar	*Visual	NONE	<b>NONE</b>	---	---
Debris	scalar	*Visual	NONE	<b>NONE</b>	---	---
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	---	---
Appearance	scalar	*Visual	NORML	<b>NORML</b>	---	---
Odor	scalar	*Visual	NORML	<b>NORML</b>	---	---
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	---	---

## FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>3</b>	---	---
Boron	ppm	ASTM D5185m		<b>411</b>	---	---
Barium	ppm	ASTM D5185m		<b>0</b>	---	---
Molybdenum	ppm	ASTM D5185m		<b>80</b>	---	---
Manganese	ppm	ASTM D5185m		<b>1</b>	---	---
Magnesium	ppm	ASTM D5185m		<b>479</b>	---	---
Calcium	ppm	ASTM D5185m		<b>1494</b>	---	---
Phosphorus	ppm	ASTM D5185m		<b>1095</b>	---	---
Zinc	ppm	ASTM D5185m		<b>1273</b>	---	---
Sulfur	ppm	ASTM D5185m		<b>3145</b>	---	---
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>14.7</b>	---	---
Base Number (BN)	mg KOH/g	ASTM D2896	10	<b>6.1</b>	---	---
Visc @ 100°C	cSt	ASTM D445	14.9	<b>14.7</b>	---	---



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : KT0001387 **Received** : 21 Jun 2024  
**Lab Number** : 06217467 **Tested** : 24 Jun 2024  
**Unique Number** : 11090331 **Diagnosed** : 24 Jun 2024 - Wes Davis  
**Test Package** : CONST ( Additional Tests: TBN )

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

**FIVE 7 EQUIPMENT**  
 1805 E 8TH ST  
 CHANDLER, OK  
 US 74834  
 Contact: JOSH  
 JOSH@FIVE7EQUIPMENT.COM  
 T:  
 F: