



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
514092
 Component
Diesel Engine
 Fluid
CHEVRON DELO 400 XLE 15W40 (--- GAL)

RECOMMENDATION

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0122768	GFL0110956	---
Sample Date		Client Info		16 Jun 2024	05 Apr 2024	---
Machine Age	hrs	Client Info		1078	578	---
Oil Age	hrs	Client Info		530	578	---
Filter Age	hrs	Client Info		530	578	---
Oil Changed		Client Info		Changed	Changed	---
Filter Changed		Client Info		Changed	Changed	---
Sample Status				NORMAL	NORMAL	---

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	31	43	---
Chromium	ppm	ASTM D5185m	>20	2	2	---
Nickel	ppm	ASTM D5185m	>4	1	1	---
Titanium	ppm	ASTM D5185m		3	<1	---
Silver	ppm	ASTM D5185m	>3	<1	<1	---
Aluminum	ppm	ASTM D5185m	>20	24	9	---
Lead	ppm	ASTM D5185m	>40	2	2	---
Copper	ppm	ASTM D5185m	>330	10	42	---
Tin	ppm	ASTM D5185m	>15	2	2	---
Vanadium	ppm	ASTM D5185m		<1	<1	---
White Metal	scalar	*Visual	NONE	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	---

CONTAMINATION










Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. No other contaminants were detected in the oil.

Silicon	ppm	ASTM D5185m	>25	16	50	---
Potassium	ppm	ASTM D5185m	>20	56	40	---
Fuel		WC Method	>5	<1.0	<1.0	---
Water		WC Method	>0.2	NEG	NEG	---
Glycol		WC Method		NEG	NEG	---
Soot %	%	*ASTM D7844	>3	0.5	0.2	---
Nitration	Abs/cm	*ASTM D7624	>20	8.7	9.6	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	23.3	20.7	---
Silt	scalar	*Visual	NONE	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	---

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		4	4	---
Boron	ppm	ASTM D5185m		166	67	---
Barium	ppm	ASTM D5185m		2	6	---
Molybdenum	ppm	ASTM D5185m		76	12	---
Manganese	ppm	ASTM D5185m		2	6	---
Magnesium	ppm	ASTM D5185m		476	751	---
Calcium	ppm	ASTM D5185m		1391	1351	---
Phosphorus	ppm	ASTM D5185m	760	917	729	---
Zinc	ppm	ASTM D5185m	830	1137	876	---
Sulfur	ppm	ASTM D5185m	2770	2856	2969	---
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.3	17.4	---
Base Number (BN)	mg KOH/g	ASTM D2896	10.7	5.9	6.3	---
Visc @ 100°C	cSt	ASTM D445	14.9	13.1	11.3	---



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0122768 **Received** : 24 Jun 2024
Lab Number : **06217804** **Tested** : 25 Jun 2024
Unique Number : 11096001 **Diagnosed** : 25 Jun 2024 - Don Baldrige
Test Package : FLEET

GFL Environmental - 629 - Northern A1
 3947 US 131 N
 Kalkaska, MI
 US 49646-8428
 Contact: MITCH HERSHBERGER

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (231)624-0848

F: