



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
910093
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0115767	GFL0115790	GFL0115784
Sample Date		Client Info		14 Jun 2024	31 May 2024	13 May 2024
Machine Age	hrs	Client Info		8651	8554	8431
Oil Age	hrs	Client Info		220	123	1436
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	Not Changed	Changed
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	9	10	27
Chromium	ppm	ASTM D5185m	>20	2	<1	6
Nickel	ppm	ASTM D5185m	>4	<1	<1	3
Titanium	ppm	ASTM D5185m		<1	<1	2
Silver	ppm	ASTM D5185m	>3	<1	0	3
Aluminum	ppm	ASTM D5185m	>20	3	4	8
Lead	ppm	ASTM D5185m	>40	<1	0	2
Copper	ppm	ASTM D5185m	>330	<1	3	3
Tin	ppm	ASTM D5185m	>15	<1	<1	3
Vanadium	ppm	ASTM D5185m		<1	0	2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	5	6	10
Potassium	ppm	ASTM D5185m	>20	3	2	7
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.4	0.4	0.8
Nitration	Abs/cm	*ASTM D7624	>20	6.2	6.7	8.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.1	17.7	20.2
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		2	4	8
Boron	ppm	ASTM D5185m	0	21	16	37
Barium	ppm	ASTM D5185m	0	1	0	1
Molybdenum	ppm	ASTM D5185m	60	72	76	99
Manganese	ppm	ASTM D5185m	0	<1	<1	3
Magnesium	ppm	ASTM D5185m	1010	820	855	1077
Calcium	ppm	ASTM D5185m	1070	1081	1112	1384
Phosphorus	ppm	ASTM D5185m	1150	914	817	1164
Zinc	ppm	ASTM D5185m	1270	1094	1097	1406
Sulfur	ppm	ASTM D5185m	2060	2821	2729	3722
Oxidation	Abs/.1mm	*ASTM D7414	>25	13.5	13.1	15.5
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	7.8	8.2	7.5
Visc @ 100°C	cSt	ASTM D445	15.4	12.7	13.2	12.6



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0115767
Lab Number : 06217827
Unique Number : 11096024
Test Package : FLEET

Received : 24 Jun 2024
Tested : 25 Jun 2024
Diagnosed : 25 Jun 2024 - Wes Davis

GFL Environmental - 180 - Tuscaloosa Hauling
 4701 12TH ST NE
 Tuscaloosa, AL
 US 35404

Contact: FREDERICK ROGERS
 fred.rogers@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: