



WEAR	NORMAL
CONTAMINATION	ABNORMAL
FLUID CONDITION	NORMAL

Area
CSP
Machine Id
CSP (S/N STEERING SYSTEM)
Component
Hydraulic System
Fluid
CHEVRON HYDRAULIC AW ISO 68 (150 GAL)

RECOMMENDATION

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		MW0061159	MW0061195	MW0055019
Sample Date		Client Info		15 May 2024	14 Feb 2024	17 Dec 2023
Machine Age	hrs	Client Info		22937	0	10768
Oil Age	hrs	Client Info		22937	20743	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Chngd	N/A	Not Chngd
Filter Changed		Client Info		N/A	N/A	Not Chngd
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>20	8	8	8
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>10	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>10	<1	0	<1
Lead	ppm	ASTM D5185m	>20	0	0	0
Copper	ppm	ASTM D5185m	>20	5	4	5
Tin	ppm	ASTM D5185m	>10	<1	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION










There is a high amount of silt (particulates < 14 microns in size) present in the oil.

Silicon	ppm	ASTM D5185m	>15	1	<1	<1
Potassium	ppm	ASTM D5185m	>20	2	0	2
Water		WC Method	>0.05	NEG	NEG	NEG
Particles >4µm		ASTM D7647		31402	77673	73557
Particles >6µm		ASTM D7647	>1300	▲ 2921	▲ 7893	▲ 6802
Particles >14µm		ASTM D7647	>160	20	▲ 287	▲ 194
Particles >21µm		ASTM D7647	>40	3	▲ 59	▲ 48
Particles >38µm		ASTM D7647	>10	0	3	3
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>-/17/14	▲ 22/19/11	▲ 23/20/15	▲ 23/20/15
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	LIGHT	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG

FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		2	<1	<1
Boron	ppm	ASTM D5185m		<1	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		<1	<1	0
Manganese	ppm	ASTM D5185m		<1	0	<1
Magnesium	ppm	ASTM D5185m		0	0	1
Calcium	ppm	ASTM D5185m		158	152	151
Phosphorus	ppm	ASTM D5185m		339	310	319
Zinc	ppm	ASTM D5185m		416	368	406
Sulfur	ppm	ASTM D5185m		1017	944	853
Acid Number (AN)	mg KOH/g	ASTM D8045		0.35	0.79	0.29
Visc @ 40°C	cSt	ASTM D445	64.6	69.7	69.7	69.7



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : MW0061159
Lab Number : 06218099
Unique Number : 11096296
Test Package : MAR 2
Received : 24 Jun 2024
Tested : 25 Jun 2024
Diagnosed : 25 Jun 2024 - Don Baldrige

AMERICAN RIVER TRANSPORTATION CO.
 P.O. BOX 2889
 ST. LOUIS, MO
 US 63111
 Contact: JOSH BARRETT
 joshua.barrett@adm.com
 T:
 F: (314)481-5278

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)