



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	SEVERE
FLUID CONDITION	ABNORMAL

Machine Id
AUTOCAR 3420Y49
 Component
Diesel Engine
 Fluid
PETRO CANADA 15W40 (17 QTS)

RECOMMENDATION

We advise that you check the fuel injection system. The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		NL0002285	NL0002042	---
Sample Date		Client Info		19 Jun 2024	24 Jan 2024	---
Machine Age	hrs	Client Info		5793	38036	---
Oil Age	hrs	Client Info		545	0	---
Filter Age	hrs	Client Info		545	0	---
Oil Changed		Client Info		Changed	Changed	---
Filter Changed		Client Info		Changed	Changed	---
Sample Status				SEVERE	ABNORMAL	---

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	45	107	---
Chromium	ppm	ASTM D5185m	>20	2	7	---
Nickel	ppm	ASTM D5185m	>4	<1	0	---
Titanium	ppm	ASTM D5185m		<1	<1	---
Silver	ppm	ASTM D5185m	>3	0	0	---
Aluminum	ppm	ASTM D5185m	>20	4	5	---
Lead	ppm	ASTM D5185m	>40	1	0	---
Copper	ppm	ASTM D5185m	>330	4	119	---
Tin	ppm	ASTM D5185m	>15	<1	<1	---
Vanadium	ppm	ASTM D5185m		<1	0	---
White Metal	scalar	*Visual	NONE	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	---

CONTAMINATION









There is a high amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

Silicon	ppm	ASTM D5185m	>25	8	36	---
Potassium	ppm	ASTM D5185m	>20	4	11	---
Fuel	%	ASTM D3524	>5	▲ 9.2	▲ 7.7	---
Water		WC Method	>0.2	NEG	NEG	---
Glycol		WC Method		NEG	NEG	---
Soot %	%	*ASTM D7844	>3	1.3	1.5	---
Nitration	Abs/cm	*ASTM D7624	>20	10.9	12.1	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.2	22.5	---
Silt	scalar	*Visual	NONE	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	---

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

Sodium	ppm	ASTM D5185m		1	2	---
Boron	ppm	ASTM D5185m		1	7	---
Barium	ppm	ASTM D5185m		0	24	---
Molybdenum	ppm	ASTM D5185m		54	50	---
Manganese	ppm	ASTM D5185m		1	4	---
Magnesium	ppm	ASTM D5185m		893	787	---
Calcium	ppm	ASTM D5185m		1083	949	---
Phosphorus	ppm	ASTM D5185m		1034	888	---
Zinc	ppm	ASTM D5185m		1267	1034	---
Sulfur	ppm	ASTM D5185m		3412	2566	---
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.8	20.5	---
Base Number (BN)	mg KOH/g	ASTM D2896		7.7	7.1	---
Visc @ 100°C	cSt	ASTM D445		▲ 12.1	▲ 12.3	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : NL0002285

Lab Number : 06219032

Unique Number : 11097229

Test Package : FLEET (Additional Tests: PercentFuel)

Received : 24 Jun 2024

Tested : 26 Jun 2024

Diagnosed : 26 Jun 2024 - Wes Davis

KIRK NATIONALEASE - SHOP 49

601 England Rd.

Lincoln, AL

US 35096

Contact: Skip Womack

shop49@knl.cc

T: (205)548-3004

F: (205)548-3006

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)