



# OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**1477**  
 Component  
**Gasoline Engine**  
 Fluid  
**GASOLINE ENGINE OIL SAE 5W30 (--- QTS)**

## RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>WC0916496</b>	WC0854079	WC0767564
Sample Date		Client Info		<b>08 Jun 2024</b>	31 Oct 2023	07 Jan 2023
Machine Age	mls	Client Info		<b>128273</b>	97022	60942
Oil Age	mls	Client Info		<b>14144</b>	6211	10918
Filter Age	mls	Client Info		<b>14144</b>	6211	10918
Oil Changed		Client Info		<b>Changed</b>	Changed	Changed
Filter Changed		Client Info		<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

## WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>150	<b>21</b>	16	15
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>5	<b>0</b>	<1	0
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	6
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	<1
Aluminum	ppm	ASTM D5185m	>40	<b>2</b>	4	3
Lead	ppm	ASTM D5185m	>50	<b>0</b>	0	0
Copper	ppm	ASTM D5185m	>155	<b>&lt;1</b>	<1	<1
Tin	ppm	ASTM D5185m	>10	<b>0</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

## CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>30	<b>7</b>	8	6
Potassium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	1	2
Fuel		WC Method	>4.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844		<b>0.1</b>	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	<b>11.7</b>	10.9	9.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>22.3</b>	21.6	19.2
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

## FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>400	<b>3</b>	1	0
Boron	ppm	ASTM D5185m	75	<b>14</b>	50	109
Barium	ppm	ASTM D5185m	5	<b>0</b>	0	1
Molybdenum	ppm	ASTM D5185m	100	<b>137</b>	158	63
Manganese	ppm	ASTM D5185m		<b>4</b>	3	<1
Magnesium	ppm	ASTM D5185m	12	<b>625</b>	685	545
Calcium	ppm	ASTM D5185m	2100	<b>1171</b>	1200	1110
Phosphorus	ppm	ASTM D5185m	650	<b>630</b>	642	635
Zinc	ppm	ASTM D5185m	850	<b>779</b>	830	737
Sulfur	ppm	ASTM D5185m	2500	<b>2658</b>	2711	2443
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>17.2</b>	15.0	12.5
Base Number (BN)	mg KOH/g	ASTM D2896		<b>5.4</b>	5.4	7.1
Visc @ 100°C	cSt	ASTM D445	10.9	<b>9.3</b>	9.3	9.4



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0916496  
**Lab Number** : 06219183  
**Unique Number** : 11097380  
**Test Package** : FLEET  
**Received** : 24 Jun 2024  
**Tested** : 25 Jun 2024  
**Diagnosed** : 25 Jun 2024 - Wes Davis

**CARCO TRANSPORTATION**  
 3403 EAST ROOSEVELT ROAD  
 LITTLE ROCK, AR  
 US 72206  
 Contact: DENNIS CATES  
 denniscales@carcotrans.com  
 T: (800)967-0777  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)