



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**1926740**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (35 QTS)**

**RECOMMENDATION**

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>PCA0124568</b>	PCA0114767	PCA0099919
Sample Date		Client Info		<b>15 Apr 2024</b>	11 Feb 2024	04 Jun 2023
Machine Age	mls	Client Info		<b>355177</b>	0	0
Oil Age	mls	Client Info		<b>37454</b>	20000	40000
Filter Age	mls	Client Info		<b>37454</b>	20000	20000
Oil Changed		Client Info		<b>Changed</b>	Not Changed	Changed
Filter Changed		Client Info		<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	<b>32</b>	19	31
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>4	<b>1</b>	<1	1
Titanium	ppm	ASTM D5185m		<b>42</b>	36	6
Silver	ppm	ASTM D5185m	>3	<b>0</b>	<1	0
Aluminum	ppm	ASTM D5185m	>20	<b>5</b>	2	2
Lead	ppm	ASTM D5185m	>40	<b>&lt;1</b>	2	2
Copper	ppm	ASTM D5185m	>330	<b>8</b>	5	8
Tin	ppm	ASTM D5185m	>15	<b>0</b>	1	2
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	<b>6</b>	5	5
Potassium	ppm	ASTM D5185m	>20	<b>7</b>	5	4
Fuel		WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>3	<b>0.5</b>	0.4	0.5
Nitration	Abs/cm	*ASTM D7624	>20	<b>9.7</b>	9.0	9.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>22.9</b>	20.5	21.2
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>11</b>	6	14
Boron	ppm	ASTM D5185m	2	<b>12</b>	21	2
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	50	<b>30</b>	25	59
Manganese	ppm	ASTM D5185m	0	<b>1</b>	1	<1
Magnesium	ppm	ASTM D5185m	950	<b>687</b>	559	901
Calcium	ppm	ASTM D5185m	1050	<b>1481</b>	1364	1211
Phosphorus	ppm	ASTM D5185m	995	<b>1025</b>	910	988
Zinc	ppm	ASTM D5185m	1180	<b>1238</b>	1030	1246
Sulfur	ppm	ASTM D5185m	2600	<b>3882</b>	3609	3034
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>17.9</b>	16.0	17.3
Base Number (BN)	mg KOH/g	ASTM D2896		<b>5.2</b>	6.3	6.3
Visc @ 100°C	cSt	ASTM D445	12.00	<b>10.9</b>	10.9	10.9


**FT-IR (Direct Trend)**




**Ferrous Alloys**




**Base Number**




**Viscosity @ 100°C**




**Non-ferrous Metals**



**Viscosity @ 100°C**



**Base Number**



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0124568  
**Lab Number** : 06219423  
**Unique Number** : 11097620  
**Test Package** : FLEET

**Received** : 25 Jun 2024  
**Tested** : 25 Jun 2024  
**Diagnosed** : 25 Jun 2024 - Wes Davis

**PERDUE FARMS - GEORGETOWN**  
 20621 SAVANAH RD  
 GEORGETOWN, DE  
 US 19947

Contact: ROBERT LOCKWOOD  
 Robert.Lockwood@Perdue.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: