



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**814018**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0122999</b>	GFL0119376	GFL0119405
Sample Date		Client Info		<b>20 Jun 2024</b>	08 May 2024	24 Apr 2024
Machine Age	hrs	Client Info		<b>849</b>	618	538
Oil Age	hrs	Client Info		<b>231</b>	80	180
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Changed</b>	Changed	Changed
Filter Changed		Client Info		<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	ATTENTION	ATTENTION

**WEAR**

Metal levels are typical for a new component breaking in.

Iron	ppm	ASTM D5185m	>100	<b>7</b>	34	30
Chromium	ppm	ASTM D5185m	>20	<b>0</b>	1	<1
Nickel	ppm	ASTM D5185m	>4	<b>&lt;1</b>	8	6
Titanium	ppm	ASTM D5185m		<b>0</b>	<1	0
Silver	ppm	ASTM D5185m	>3	<b>1</b>	<1	<1
Aluminum	ppm	ASTM D5185m	>20	<b>2</b>	6	6
Lead	ppm	ASTM D5185m	>40	<b>0</b>	<1	0
Copper	ppm	ASTM D5185m	>330	<b>50</b>	258	248
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	4	3
Vanadium	ppm	ASTM D5185m		<b>0</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>9</b>	60	59
Potassium	ppm	ASTM D5185m	>20	<b>4</b>	8	3
Fuel		WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>3	<b>0.2</b>	0.4	0.4
Nitration	Abs/cm	*ASTM D7624	>20	<b>6.4</b>	9.8	9.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>19.6</b>	24.0	23.6
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>3</b>	<1	2
Boron	ppm	ASTM D5185m	0	<b>20</b>	204	235
Barium	ppm	ASTM D5185m	0	<b>0</b>	<1	1
Molybdenum	ppm	ASTM D5185m	60	<b>64</b>	118	121
Manganese	ppm	ASTM D5185m	0	<b>1</b>	4	4
Magnesium	ppm	ASTM D5185m	1010	<b>967</b>	696	752
Calcium	ppm	ASTM D5185m	1070	<b>1099</b>	1368	1424
Phosphorus	ppm	ASTM D5185m	1150	<b>999</b>	733	732
Zinc	ppm	ASTM D5185m	1270	<b>1240</b>	873	868
Sulfur	ppm	ASTM D5185m	2060	<b>3434</b>	2681	2619
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>15.1</b>	22.0	21.2
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>8.5</b>	7.6	7.7
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.7</b>	10.3	10.2



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0122999  
**Lab Number** : 06220505  
**Unique Number** : 11098702  
**Test Package** : FLEET

**Received** : 25 Jun 2024  
**Tested** : 26 Jun 2024  
**Diagnosed** : 26 Jun 2024 - Wes Davis

**GFL Environmental - 814 - Little Rock Hauling**  
 4005 Hwy 161 N.  
 Little Rock, AR  
 US 72117  
 Contact: Brad Koenig  
 bkoenig@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: