



LIEBHERR

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
LIEBHERR LH50 1216-123739
Component
Diesel Engine
Fluid
MOBIL DELVAC 1 5W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LH0211710	LH0211706	LH0211682
Sample Date		Client Info		17 Jun 2024	10 Apr 2024	31 Jan 2024
Machine Age	hrs	Client Info		12322	11545	10743
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>66	2	3	19
Chromium	ppm	ASTM D5185m	>4	0	0	0
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>8	3	2	2
Lead	ppm	ASTM D5185m	>10	1	1	<1
Copper	ppm	ASTM D5185m	>74	2	2	1
Tin	ppm	ASTM D5185m	>4	0	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION












There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>15	12	12	12
Potassium	ppm	ASTM D5185m	>20	3	1	0
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.1	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	11.4	11.1	10.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	40.2	40.0	38.8
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		1	2	<1
Boron	ppm	ASTM D5185m	291	50	87	77
Barium	ppm	ASTM D5185m	0.0	<1	0	0
Molybdenum	ppm	ASTM D5185m	8.0	43	44	45
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	624	897	871	904
Calcium	ppm	ASTM D5185m	2158	1015	1014	1002
Phosphorus	ppm	ASTM D5185m	1132	1020	1053	1054
Zinc	ppm	ASTM D5185m	1300	1273	1224	1270
Sulfur	ppm	ASTM D5185m	3616	3335	3399	3138
Oxidation	Abs/.1mm	*ASTM D7414	>25	48.9	49.2	46.9
Base Number (BN)	mg KOH/g	ASTM D2896	11.0	4.2	3.9	4.9
Visc @ 100°C	cSt	ASTM D445	15.0	13.1	12.8	13.1



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LH0211710 **Received** : 25 Jun 2024
Lab Number : 06220547 **Tested** : 26 Jun 2024
Unique Number : 11098744 **Diagnosed** : 27 Jun 2024 - Don Baldrige
Test Package : MOBCE (Additional Tests: TBN)

AHLSTROM-MUNKSJO NA SPECIALTY
 PO BOX 600
 KAUKAUNA, WI
 US 54130
 Contact: JOE SEITZ
 joe.seitz@ahlstrom-munksjo.com
 T:
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)