



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
PETERBILT 9571603
Component
Diesel Engine
Fluid
MOBIL DELVAC 1300 SUPER 15W40 (45 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		RPL0018010	RPL0006311	RPL0000963
Sample Date		Client Info		21 Jun 2024	06 Mar 2023	28 Jun 2022
Machine Age	mls	Client Info		225627	156934	112351
Oil Age	mls	Client Info		24969	31114	42812
Filter Age	mls	Client Info		24969	31114	42812
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	11	16	41
Chromium	ppm	ASTM D5185m	>20	0	<1	<1
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m	>3	0	0	<1
Aluminum	ppm	ASTM D5185m	>20	6	7	7
Lead	ppm	ASTM D5185m	>40	0	1	2
Copper	ppm	ASTM D5185m	>330	2	2	4
Tin	ppm	ASTM D5185m	>15	0	<1	1
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	7	9	7
Potassium	ppm	ASTM D5185m	>20	6	10	12
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.5	0.6	0.8
Nitration	Abs/cm	*ASTM D7624	>20	11.1	11.6	12.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.6	24.5	28.6
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		2	2	1
Boron	ppm	ASTM D5185m	0	19	57	43
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	0	126	55	50
Manganese	ppm	ASTM D5185m		<1	1	<1
Magnesium	ppm	ASTM D5185m	0	730	572	696
Calcium	ppm	ASTM D5185m		1260	1593	1436
Phosphorus	ppm	ASTM D5185m		751	762	721
Zinc	ppm	ASTM D5185m		901	1021	891
Sulfur	ppm	ASTM D5185m		3533	2617	3143
Oxidation	Abs/.1mm	*ASTM D7414	>25	19.1	24.5	23.3
Base Number (BN)	mg KOH/g	ASTM D2896	9.4	4.7	7.0	7.2
Visc @ 100°C	cSt	ASTM D445	14	13.2	13.9	15.2



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : RPL0018010 **Received** : 26 Jun 2024
Lab Number : 06220627 **Tested** : 27 Jun 2024
Unique Number : 11098824 **Diagnosed** : 27 Jun 2024 - Wes Davis
Test Package : FLEET

RTL PACLEASE - 7004 - Austin
 1205 Smith Road
 Austin, TX
 US 78721
 Contact: David Johnson
 JohnsonD@RushEnterprises.com
 T: (512)401-7063
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)