



# OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**PETERBILT 9571693**  
 Component  
**Diesel Engine**  
 Fluid  
**{not provided} (44 QTS)**

## RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>RPL0019833</b>	---	---
Sample Date		Client Info		<b>21 Jun 2024</b>	---	---
Machine Age	mls	Client Info		<b>78348</b>	---	---
Oil Age	mls	Client Info		<b>35058</b>	---	---
Filter Age	mls	Client Info		<b>35058</b>	---	---
Oil Changed		Client Info		<b>Changed</b>	---	---
Filter Changed		Client Info		<b>Changed</b>	---	---
Sample Status				<b>NORMAL</b>	---	---

## WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>110	<b>37</b>	---	---
Chromium	ppm	ASTM D5185m	>4	<b>2</b>	---	---
Nickel	ppm	ASTM D5185m	>2	<b>0</b>	---	---
Titanium	ppm	ASTM D5185m		<b>0</b>	---	---
Silver	ppm	ASTM D5185m	>2	<b>&lt;1</b>	---	---
Aluminum	ppm	ASTM D5185m	>25	<b>10</b>	---	---
Lead	ppm	ASTM D5185m	>45	<b>4</b>	---	---
Copper	ppm	ASTM D5185m	>85	<b>6</b>	---	---
Tin	ppm	ASTM D5185m	>4	<b>1</b>	---	---
Vanadium	ppm	ASTM D5185m		<b>0</b>	---	---
White Metal	scalar	*Visual	NONE	<b>NONE</b>	---	---
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	---	---

## CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>30	<b>15</b>	---	---
Potassium	ppm	ASTM D5185m	>20	<b>27</b>	---	---
Fuel		WC Method	>5	<b>&lt;1.0</b>	---	---
Water		WC Method	>0.2	<b>NEG</b>	---	---
Glycol		WC Method		<b>NEG</b>	---	---
Soot %	%	*ASTM D7844	>3	<b>0.4</b>	---	---
Nitration	Abs/cm	*ASTM D7624	>20	<b>12.1</b>	---	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>24.7</b>	---	---
Silt	scalar	*Visual	NONE	<b>NONE</b>	---	---
Debris	scalar	*Visual	NONE	<b>NONE</b>	---	---
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	---	---
Appearance	scalar	*Visual	NORML	<b>NORML</b>	---	---
Odor	scalar	*Visual	NORML	<b>NORML</b>	---	---
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	---	---

## FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>4</b>	---	---
Boron	ppm	ASTM D5185m		<b>29</b>	---	---
Barium	ppm	ASTM D5185m		<b>&lt;1</b>	---	---
Molybdenum	ppm	ASTM D5185m		<b>100</b>	---	---
Manganese	ppm	ASTM D5185m		<b>2</b>	---	---
Magnesium	ppm	ASTM D5185m		<b>685</b>	---	---
Calcium	ppm	ASTM D5185m		<b>1418</b>	---	---
Phosphorus	ppm	ASTM D5185m		<b>757</b>	---	---
Zinc	ppm	ASTM D5185m		<b>911</b>	---	---
Sulfur	ppm	ASTM D5185m		<b>3263</b>	---	---
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>25.4</b>	---	---
Base Number (BN)	mg KOH/g	ASTM D2896		<b>4.7</b>	---	---
Visc @ 100°C	cSt	ASTM D445		<b>12.9</b>	---	---



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : RPL0019833  
**Lab Number** : 06220642  
**Unique Number** : 11098839  
**Test Package** : FLEET

**Received** : 26 Jun 2024  
**Tested** : 27 Jun 2024  
**Diagnosed** : 27 Jun 2024 - Angela Borella

**RTL PACLEASE - 7018 - West Texas**  
 1230 South Grandview  
 Odessa, TX  
 US 79761

Contact: David Johnson  
 JohnsonD@RushEnterprises.com

T: (512)401-7063

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: