



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
INTERNATIONAL 5012905
Component
Diesel Engine
Fluid
VALVOLINE 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		IL0036661	IL0035038	IL0034244
Sample Date		Client Info		17 Jun 2024	19 Mar 2024	21 Dec 2023
Machine Age	mls	Client Info		348337	329427	311877
Oil Age	mls	Client Info		0	0	0
Filter Age	mls	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	18	▲ 129	19
Chromium	ppm	ASTM D5185m	>20	<1	7	<1
Nickel	ppm	ASTM D5185m	>4	0	4	0
Titanium	ppm	ASTM D5185m		<1	1	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	5	18	5
Lead	ppm	ASTM D5185m	>40	0	▲ 68	0
Copper	ppm	ASTM D5185m	>330	1	8	<1
Tin	ppm	ASTM D5185m	>15	0	1	0
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	5	17	5
Potassium	ppm	ASTM D5185m	>20	4	43	4
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.3	2.2	0.4
Nitration	Abs/cm	*ASTM D7624	>20	12.9	16.2	11.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	24.7	37.4	23.9
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		3	6	2
Boron	ppm	ASTM D5185m	39	20	10	97
Barium	ppm	ASTM D5185m	1	0	0	0
Molybdenum	ppm	ASTM D5185m	49	65	99	86
Manganese	ppm	ASTM D5185m	1	<1	2	0
Magnesium	ppm	ASTM D5185m	616	810	478	619
Calcium	ppm	ASTM D5185m	1554	1312	1551	1394
Phosphorus	ppm	ASTM D5185m	899	761	1099	887
Zinc	ppm	ASTM D5185m	1069	981	1661	1105
Sulfur	ppm	ASTM D5185m	2624	2828	3225	3050
Oxidation	Abs/.1mm	*ASTM D7414	>25	24.1	35.1	20.7
Base Number (BN)	mg KOH/g	ASTM D2896	6.9	4.9	▲ 2.3	5.6
Visc @ 100°C	cSt	ASTM D445	13.6	12.9	13.5	12.6



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : IL0036661
Lab Number : 06220673
Unique Number : 11098870
Test Package : FLEET

Received : 26 Jun 2024
Tested : 27 Jun 2024
Diagnosed : 27 Jun 2024 - Wes Davis

TAMPA IDEALEASE
 5951 ORIENT ROAD
 TAMPA, FL
 US 33610-9565
 Contact: Russ Cook
 russcook@idealease.com
 T: (813)626-9285
 F: (844)270-1356

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)