



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	ATTENTION

Machine Id
1342
 Component
Diesel Engine
 Fluid
DIESEL ENGINE OIL SAE 15W40 (--- QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0948957	WC0870835	WC0743013
Sample Date		Client Info		13 Jun 2024	18 Jan 2024	28 Sep 2022
Machine Age	mls	Client Info		244215	234111	214144
Oil Age	mls	Client Info		0	0	0
Filter Age	mls	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				ATTENTION	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	70	17	29
Chromium	ppm	ASTM D5185m	>20	5	1	1
Nickel	ppm	ASTM D5185m	>4	0	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	5	5	4
Lead	ppm	ASTM D5185m	>40	1	0	<1
Copper	ppm	ASTM D5185m	>330	64	<1	2
Tin	ppm	ASTM D5185m	>15	0	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION












There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	17	6	8
Potassium	ppm	ASTM D5185m	>20	3	4	15
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.8	0.4	0.4
Nitration	Abs/cm	*ASTM D7624	>20	11.4	9.3	9.3
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.2	18.4	19.7
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The oil viscosity is higher than normal. The BN result indicates that there is suitable alkalinity remaining in the oil.

Sodium	ppm	ASTM D5185m	>158	4	4	18
Boron	ppm	ASTM D5185m	250	38	42	22
Barium	ppm	ASTM D5185m	10	1	0	2
Molybdenum	ppm	ASTM D5185m	100	66	87	59
Manganese	ppm	ASTM D5185m		3	0	<1
Magnesium	ppm	ASTM D5185m	450	194	132	96
Calcium	ppm	ASTM D5185m	3000	1410	2104	2157
Phosphorus	ppm	ASTM D5185m	1150	707	1103	971
Zinc	ppm	ASTM D5185m	1350	822	1304	1178
Sulfur	ppm	ASTM D5185m	4250	2666	4244	4194
Oxidation	Abs/.1mm	*ASTM D7414	>25	19.5	13.9	13.9
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	5.5	6.9	8.6
Visc @ 100°C	cSt	ASTM D445	14.4	19.5	13.6	14.1



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0948957 **Received** : 26 Jun 2024
Lab Number : 06220866 **Tested** : 27 Jun 2024
Unique Number : 11099063 **Diagnosed** : 27 Jun 2024 - Don Baldrige
Test Package : MOB 1 (Additional Tests: TBN)

WAKE COUNTY PUBLIC SCHOOL SYSTEM
 1551 ROCK QUARRY ROAD
 RALEIGH, NC
 US 27610
 Contact: DEVIN WEBER
 dweber@wcpss.net
 T: (919)856-8076
 F: x:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)