



# OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	SEVERE
FLUID CONDITION	ABNORMAL

Machine Id  
**1429**  
Component  
**Diesel Engine**  
Fluid  
**DIESEL ENGINE OIL SAE 15W40 (--- QTS)**

## RECOMMENDATION

We advise that you check the fuel injection system. We recommend that you drain the oil from the component if this has not already been done. We recommend an early resample to monitor this condition. Please specify the component make and model with your next sample.

## WEAR

All component wear rates are normal.













## CONTAMINATION

There is a high amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

## FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The oil is no longer serviceable due to the presence of contaminants.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>WC0948972</b>	WC0870692	WC0761241
Sample Date		Client Info		<b>10 Jun 2024</b>	03 Jan 2024	15 Dec 2022
Machine Age	mls	Client Info		<b>261317</b>	0	229274
Oil Age	mls	Client Info		<b>0</b>	0	0
Filter Age	mls	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Not Changd</b>	Not Changd	Not Changd
Filter Changed		Client Info		<b>N/A</b>	Not Changd	Not Changd
Sample Status				<b>SEVERE</b>	SEVERE	NORMAL
Iron	ppm	ASTM D5185m	>100	<b>8</b>	11	12
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>4	<b>0</b>	<1	<1
Titanium	ppm	ASTM D5185m		<b>0</b>	0	0
Silver	ppm	ASTM D5185m	>3	<b>0</b>	0	<1
Aluminum	ppm	ASTM D5185m	>20	<b>5</b>	5	5
Lead	ppm	ASTM D5185m	>40	<b>0</b>	0	<1
Copper	ppm	ASTM D5185m	>330	<b>&lt;1</b>	<1	<1
Tin	ppm	ASTM D5185m	>15	<b>0</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	<1
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Silicon	ppm	ASTM D5185m	>25	<b>4</b>	4	5
Potassium	ppm	ASTM D5185m	>20	<b>4</b>	3	3
Fuel	%	ASTM D3524	>5	<b>▲ 10.8</b>	▲ 9.3	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>3	<b>0.6</b>	0.6	0.4
Nitration	Abs/cm	*ASTM D7624	>20	<b>10.4</b>	10.0	9.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>19.5</b>	18.9	18.2
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG
Sodium	ppm	ASTM D5185m	>158	<b>1</b>	2	2
Boron	ppm	ASTM D5185m	250	<b>24</b>	31	47
Barium	ppm	ASTM D5185m	10	<b>0</b>	3	1
Molybdenum	ppm	ASTM D5185m	100	<b>78</b>	73	75
Manganese	ppm	ASTM D5185m		<b>0</b>	0	<1
Magnesium	ppm	ASTM D5185m	450	<b>56</b>	99	40
Calcium	ppm	ASTM D5185m	3000	<b>1860</b>	1731	2106
Phosphorus	ppm	ASTM D5185m	1150	<b>849</b>	865	985
Zinc	ppm	ASTM D5185m	1350	<b>1118</b>	1050	1220
Sulfur	ppm	ASTM D5185m	4250	<b>3187</b>	3377	4313
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>15.5</b>	15.4	13.0
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	<b>6.4</b>	6.9	7.4
Visc @ 100°C	cSt	ASTM D445	14.4	<b>▲ 11.3</b>	▲ 11.3	13.1



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0948972 **Received** : 26 Jun 2024  
**Lab Number** : 06220941 **Tested** : 01 Jul 2024  
**Unique Number** : 11099138 **Diagnosed** : 01 Jul 2024 - Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: PercentFuel, TBN )

**WAKE COUNTY PUBLIC SCHOOL SYSTEM**  
 1551 ROCK QUARRY ROAD  
 RALEIGH, NC  
 US 27610  
 Contact: DEVIN WEBER  
 dweber@wcpss.net  
 T: (919)856-8076  
 F: x:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)