



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
611345
 Component
Diesel Engine
 Fluid
DIESEL ENGINE OIL SAE 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0936733	WC0882308	---
Sample Date		Client Info		20 Jun 2024	21 Dec 2023	---
Machine Age	mls	Client Info		56181	0	---
Oil Age	mls	Client Info		10000	0	---
Filter Age	mls	Client Info		10000	0	---
Oil Changed		Client Info		Changed	Changed	---
Filter Changed		Client Info		Changed	Changed	---
Sample Status				NORMAL	ABNORMAL	---

WEAR

Metal levels are typical for a new component breaking in.

Iron	ppm	ASTM D5185m	>100	15	59	---
Chromium	ppm	ASTM D5185m	>20	<1	1	---
Nickel	ppm	ASTM D5185m	>4	0	<1	---
Titanium	ppm	ASTM D5185m		0	<1	---
Silver	ppm	ASTM D5185m	>3	0	<1	---
Aluminum	ppm	ASTM D5185m	>20	10	25	---
Lead	ppm	ASTM D5185m	>40	1	7	---
Copper	ppm	ASTM D5185m	>330	23	107	---
Tin	ppm	ASTM D5185m	>15	<1	4	---
Vanadium	ppm	ASTM D5185m		0	0	---
White Metal	scalar	*Visual	NONE	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	---

CONTAMINATION








Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	5	11	---
Potassium	ppm	ASTM D5185m	>20	21	74	---
Fuel		WC Method	>5	<1.0	0.9	---
Water		WC Method	>0.2	NEG	NEG	---
Glycol		WC Method		NEG	NEG	---
Soot %	%	*ASTM D7844	>3	0.3	0.4	---
Nitration	Abs/cm	*ASTM D7624	>20	10.4	10.7	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	25.7	28.9	---
Silt	scalar	*Visual	NONE	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	---

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>158	1	0	---
Boron	ppm	ASTM D5185m	250	89	19	---
Barium	ppm	ASTM D5185m	10	0	9	---
Molybdenum	ppm	ASTM D5185m	100	125	95	---
Manganese	ppm	ASTM D5185m		0	3	---
Magnesium	ppm	ASTM D5185m	450	638	444	---
Calcium	ppm	ASTM D5185m	3000	1511	1508	---
Phosphorus	ppm	ASTM D5185m	1150	623	1024	---
Zinc	ppm	ASTM D5185m	1350	903	1274	---
Sulfur	ppm	ASTM D5185m	4250	2345	2890	---
Oxidation	Abs/.1mm	*ASTM D7414	>25	22.7	26.2	---
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	6.1	▲ 3.2	---
Visc @ 100°C	cSt	ASTM D445	14.4	12.8	12.4	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0936733
Lab Number : 06220993
Unique Number : 11099190
Test Package : FLEET

Received : 26 Jun 2024
Tested : 27 Jun 2024
Diagnosed : 27 Jun 2024 - Wes Davis

SALEM NATIONALEASE CORPORATION
 198 PARK PLAZA DRIVE
 WINSTON SALEM, NC
 US 27105

Contact: Audrey Hopkins
 Audrey.Hopkins@salemcorp.com

T: (336)767-9642

F: x:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)