



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
733022
Component
Natural Gas Engine
Fluid
PETRO CANADA DURON GEO LD 15W40 (--- QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0121741	GFL0106908	GFL0092166
Sample Date		Client Info		20 Jun 2024	10 Apr 2024	01 Feb 2024
Machine Age	hrs	Client Info		3668	3052	2469
Oil Age	hrs	Client Info		600	3152	3708
Filter Age	hrs	Client Info		600	3152	3708
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>50	6	6	6
Chromium	ppm	ASTM D5185m	>4	<1	<1	<1
Nickel	ppm	ASTM D5185m	>2	0	0	1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>9	3	2	3
Lead	ppm	ASTM D5185m	>30	<1	<1	1
Copper	ppm	ASTM D5185m	>35	<1	0	2
Tin	ppm	ASTM D5185m	>4	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>+100	3	4	4
Potassium	ppm	ASTM D5185m	>20	8	4	9
Water		WC Method	>0.1	NEG	NEG	NEG
Soot %	%	*ASTM D7844		0	0	0.9
Nitration	Abs/cm	*ASTM D7624	>20	11.1	11.8	6.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.4	22.4	19.4
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		7	7	7
Boron	ppm	ASTM D5185m	50	8	7	6
Barium	ppm	ASTM D5185m	5	0	0	0
Molybdenum	ppm	ASTM D5185m	50	53	52	52
Manganese	ppm	ASTM D5185m	0	0	0	1
Magnesium	ppm	ASTM D5185m	560	547	529	531
Calcium	ppm	ASTM D5185m	1510	1607	1619	1530
Phosphorus	ppm	ASTM D5185m	780	638	674	666
Zinc	ppm	ASTM D5185m	870	995	917	935
Sulfur	ppm	ASTM D5185m	2040	2360	2617	2355
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.9	19.0	13.8
Base Number (BN)	mg KOH/g	ASTM D2896	10.2	4.6	4.5	9.6
Visc @ 100°C	cSt	ASTM D445	15.1	14.9	14.7	14.8


FT-IR (Direct Trend)




Ferrous Alloys




Base Number




Non-ferrous Metals




Viscosity @ 100°C



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0121741
Lab Number : 06220995
Unique Number : 11099192
Test Package : FLEET

Received : 26 Jun 2024
Tested : 27 Jun 2024
Diagnosed : 27 Jun 2024 - Wes Davis

GFL Environmental - 856 - Houston South
 8515 Highway 6 South
 Houston, TX
 US 77083
 Contact: Apolinar Zacarias
 pzacariascano@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: