



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
[W68119]
 Machine Id
JOHN DEERE 460P 1DW460PAEPFB06202
 Component
Center Differential
 Fluid
JOHN DEERE HY-GARD HYD/TRANS (18 GAL)

RECOMMENDATION

Resample at the next service interval to monitor. (Customer Sample Comment: W68119)

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0220221	JR0191100	---
Sample Date		Client Info		25 Jun 2024	16 Nov 2023	---
Machine Age	hrs	Client Info		1043	563	---
Oil Age	hrs	Client Info		1043	563	---
Filter Age	hrs	Client Info		0	0	---
Oil Changed		Client Info		Not Changd	N/A	---
Filter Changed		Client Info		Not Changd	N/A	---
Sample Status				NORMAL	NORMAL	---

WEAR

All component wear rates are normal.

PQ	UOM	Method	Limit/Abn	Current	History1	History2
PQ		ASTM D8184		17	26	---
Iron	ppm	ASTM D5185m	>500	31	28	---
Chromium	ppm	ASTM D5185m	>10	0	0	---
Nickel	ppm	ASTM D5185m	>10	0	0	---
Titanium	ppm	ASTM D5185m		0	<1	---
Silver	ppm	ASTM D5185m		0	0	---
Aluminum	ppm	ASTM D5185m	>25	<1	<1	---
Lead	ppm	ASTM D5185m	>25	11	6	---
Copper	ppm	ASTM D5185m	>100	10	6	---
Tin	ppm	ASTM D5185m	>10	0	0	---
Vanadium	ppm	ASTM D5185m		0	0	---
White Metal	scalar	*Visual	NONE	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	---

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	4	5	---
Potassium	ppm	ASTM D5185m	>20	<1	0	---
Water		WC Method	>.2	NEG	NEG	---
Silt	scalar	*Visual	NONE	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual	>.2	NEG	NEG	---

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		4	4	---
Boron	ppm	ASTM D5185m	6	1	0	---
Barium	ppm	ASTM D5185m	0	5	5	---
Molybdenum	ppm	ASTM D5185m	0	0	0	---
Manganese	ppm	ASTM D5185m		2	3	---
Magnesium	ppm	ASTM D5185m	145	101	102	---
Calcium	ppm	ASTM D5185m	3570	3598	3497	---
Phosphorus	ppm	ASTM D5185m	1290	1038	1046	---
Zinc	ppm	ASTM D5185m	1640	1242	1227	---
Sulfur	ppm	ASTM D5185m		4052	3477	---
Visc @ 40°C	cSt	ASTM D445	57.0	53.9	54.5	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0220221 **Received** : 26 Jun 2024
Lab Number : 06221485 **Tested** : 27 Jun 2024
Unique Number : 11099682 **Diagnosed** : 28 Jun 2024 - Sean Felton
Test Package : CONST (Additional Tests: PQ)

JRE - CHARLOTTE
 9550 STATESVILLE ROAD
 CHARLOTTE, NC
 US 28269

Contact: CHARLOTTE SHOP
 myoung@jamesriverequipment.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (704)597-0211
 F: (704)596-6198