



OIL ANALYSIS REPORT

WEAR	ABNORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
VOLVO A30G#301 (S/N 740069)
 Component
Rear Left Hub
 Fluid
MOBIL 75W90 (--- GAL)

RECOMMENDATION

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		TLY0002473	TLY0001641	TLY0001563
Sample Date		Client Info		21 Jun 2024	30 Oct 2023	04 Apr 2023
Machine Age	hrs	Client Info		7874	7291	6708
Oil Age	hrs	Client Info		7291	1291	2700
Filter Age	hrs	Client Info		7291	1291	2700
Oil Changed		Client Info		Not Changed	Not Changed	Not Changed
Filter Changed		Client Info		Not Changed	Not Changed	Not Changed
Sample Status				ABNORMAL	NORMAL	ABNORMAL

WEAR

Gear wear is indicated. All other component wear rates are normal.

Iron	ppm	ASTM D5185m	>200	▲ 201	142	98
Chromium	ppm	ASTM D5185m	>10	3	2	2
Nickel	ppm	ASTM D5185m	>10	2	<1	<1
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m		<1	0	0
Aluminum	ppm	ASTM D5185m		2	1	2
Lead	ppm	ASTM D5185m		<1	0	0
Copper	ppm	ASTM D5185m		6	3	3
Tin	ppm	ASTM D5185m		1	<1	0
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	▲ HEAVY
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION





There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m		10	13	7
Potassium	ppm	ASTM D5185m	>20	1	0	0
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	LIGHT	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		0	1	1
Boron	ppm	ASTM D5185m		47	39	43
Barium	ppm	ASTM D5185m		1	0	0
Molybdenum	ppm	ASTM D5185m		1	0	<1
Manganese	ppm	ASTM D5185m		3	2	2
Magnesium	ppm	ASTM D5185m		4	2	4
Calcium	ppm	ASTM D5185m		51	42	50
Phosphorus	ppm	ASTM D5185m		585	545	598
Zinc	ppm	ASTM D5185m		43	22	41
Sulfur	ppm	ASTM D5185m		19988	17741	21596



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : TLY0002473
Lab Number : 06221889
Unique Number : 11100086
Test Package : CONST

Received : 26 Jun 2024
Tested : 29 Jun 2024
Diagnosed : 29 Jun 2024 - Don Baldrige

GAINES & COMPANY
 112 WESTMINISTER RD
 REISTERSTOWN, MD
 US 21136

Contact: LANCE TANCRAITOR
 ltancraitor@gainesandco.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (410)833-9833

F: