



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
VOLVO A30G#301 (S/N 740069)
 Component
Front Right Hub
 Fluid
MOBIL 75W90 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		TLY0002471	TLY0001637	TLY0001559
Sample Date		Client Info		21 Jun 2024	30 Oct 2023	04 Apr 2023
Machine Age	hrs	Client Info		7874	7291	6708
Oil Age	hrs	Client Info		7291	1291	2700
Filter Age	hrs	Client Info		7291	1291	2700
Oil Changed		Client Info		Not Changed	Not Changed	Not Changed
Filter Changed		Client Info		Not Changed	Not Changed	Not Changed
Sample Status				NORMAL	ABNORMAL	ABNORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>200	176	▲ 294	▲ 288
Chromium	ppm	ASTM D5185m	>10	3	4	4
Nickel	ppm	ASTM D5185m	>10	2	2	2
Titanium	ppm	ASTM D5185m		<1	0	<1
Silver	ppm	ASTM D5185m		<1	0	0
Aluminum	ppm	ASTM D5185m		2	0	2
Lead	ppm	ASTM D5185m		<1	0	0
Copper	ppm	ASTM D5185m		6	21	19
Tin	ppm	ASTM D5185m		1	<1	<1
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	MODER
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m		9	4	6
Potassium	ppm	ASTM D5185m	>20	1	0	<1
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	LIGHT	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION


The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		0	4	4
Boron	ppm	ASTM D5185m		47	226	232
Barium	ppm	ASTM D5185m		1	0	0
Molybdenum	ppm	ASTM D5185m		1	0	<1
Manganese	ppm	ASTM D5185m		3	5	6
Magnesium	ppm	ASTM D5185m		3	0	<1
Calcium	ppm	ASTM D5185m		44	17	16
Phosphorus	ppm	ASTM D5185m		537	2392	2419
Zinc	ppm	ASTM D5185m		37	16	20
Sulfur	ppm	ASTM D5185m		18098	27795	34484


Ferrous Alloys



Non-ferrous Metals



Viscosity @ 40°C



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : TLY0002471
Lab Number : 06221892
Unique Number : 11100089
Test Package : CONST
Received : 26 Jun 2024
Tested : 29 Jun 2024
Diagnosed : 29 Jun 2024 - Don Baldrige

GAINES & COMPANY
 112 WESTMINISTER RD
 REISTERSTOWN, MD
 US 21136

Contact: LANCE TANCRAITOR
 ltancraitor@gainesandco.com
 T: (410)833-9833

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: