



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
JOHN DEERE 700k-607 (S/N 1T0700KXCHF318204)
 Component
Diesel Engine
 Fluid
MOBIL DELVAC SUPER 1400 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		TLY0002309	TLY0001675	TLY0001297
Sample Date		Client Info		21 Jun 2024	26 Aug 2023	22 Feb 2023
Machine Age	hrs	Client Info		6856	6397	5665
Oil Age	hrs	Client Info		6397	732	552
Filter Age	hrs	Client Info		6397	732	552
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>51	32	116	22
Chromium	ppm	ASTM D5185m	>11	<1	3	<1
Nickel	ppm	ASTM D5185m	>5	1	9	<1
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>3	0	0	<1
Aluminum	ppm	ASTM D5185m	>31	4	8	4
Lead	ppm	ASTM D5185m	>26	<1	0	0
Copper	ppm	ASTM D5185m	>26	2	5	1
Tin	ppm	ASTM D5185m	>4	<1	1	<1
Vanadium	ppm	ASTM D5185m		0	<1	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>22	7	17	5
Potassium	ppm	ASTM D5185m	>20	2	1	2
Fuel		WC Method	>2.1	<1.0	<1.0	<1.0
Water		WC Method	>0.21	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.5	0.6	0.5
Nitration	Abs/cm	*ASTM D7624	>20	9.2	10.3	9.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.1	21.7	21.1
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.21	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>31	5	5	2
Boron	ppm	ASTM D5185m		31	23	25
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		49	69	54
Manganese	ppm	ASTM D5185m		<1	1	<1
Magnesium	ppm	ASTM D5185m		539	665	668
Calcium	ppm	ASTM D5185m		1847	1616	1483
Phosphorus	ppm	ASTM D5185m		826	832	869
Zinc	ppm	ASTM D5185m		952	1049	1087
Sulfur	ppm	ASTM D5185m		2869	2664	3024
Oxidation	Abs/.1mm	*ASTM D7414	>25	21.0	20.9	18.9
Base Number (BN)	mg KOH/g	ASTM D2896	11.5	9.1	8.4	9.0
Visc @ 100°C	cSt	ASTM D445	15.0	13.1	13.1	12.9



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : TLY0002309 **Received** : 26 Jun 2024
Lab Number : 06221947 **Tested** : 28 Jun 2024
Unique Number : 11100144 **Diagnosed** : 28 Jun 2024 - Wes Davis
Test Package : CONST (Additional Tests: TBN)

GAINES & COMPANY
 112 WESTMINSTER RD
 REISTERSTOWN, MD
 US 21136

Contact: LANCE TANCRAITOR
 ltancairo@gainesandco.com

T: (410)833-9833

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: