



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
[W47733]
 Machine Id
JOHN DEERE 325G 1T0325GKENJ430617
 Component
Diesel Engine
 Fluid
JOHN DEERE ENGINE OIL PLUS 50 II 0W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0225412	JR0183823	---
Sample Date		Client Info		26 Jun 2024	06 Sep 2023	---
Machine Age	hrs	Client Info		635	474	---
Oil Age	hrs	Client Info		0	474	---
Filter Age	hrs	Client Info		0	474	---
Oil Changed		Client Info		Changed	Changed	---
Filter Changed		Client Info		Changed	Changed	---
Sample Status				NORMAL	ABNORMAL	---

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>51	28	41	---
Chromium	ppm	ASTM D5185m	>11	<1	<1	---
Nickel	ppm	ASTM D5185m	>5	<1	<1	---
Titanium	ppm	ASTM D5185m		<1	<1	---
Silver	ppm	ASTM D5185m	>3	0	<1	---
Aluminum	ppm	ASTM D5185m	>31	8	7	---
Lead	ppm	ASTM D5185m	>26	0	0	---
Copper	ppm	ASTM D5185m	>26	25	59	---
Tin	ppm	ASTM D5185m	>4	<1	<1	---
Vanadium	ppm	ASTM D5185m		<1	0	---
White Metal	scalar	*Visual	NONE	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	---

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>22	19	▲ 40	---
Potassium	ppm	ASTM D5185m	>20	4	2	---
Fuel		WC Method	>2.1	<1.0	<1.0	---
Water		WC Method	>0.21	NEG	NEG	---
Glycol		WC Method		NEG	NEG	---
Soot %	%	*ASTM D7844	>3	0.5	0.8	---
Nitration	Abs/cm	*ASTM D7624	>20	8.6	9.4	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	25.8	26.3	---
Silt	scalar	*Visual	NONE	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.21	NEG	NEG	---

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>31	8	11	---
Boron	ppm	ASTM D5185m		225	181	---
Barium	ppm	ASTM D5185m		2	3	---
Molybdenum	ppm	ASTM D5185m		254	242	---
Manganese	ppm	ASTM D5185m		<1	1	---
Magnesium	ppm	ASTM D5185m		836	816	---
Calcium	ppm	ASTM D5185m		1498	1728	---
Phosphorus	ppm	ASTM D5185m		952	871	---
Zinc	ppm	ASTM D5185m		1147	1142	---
Sulfur	ppm	ASTM D5185m		3440	3422	---
Oxidation	Abs/.1mm	*ASTM D7414	>25	22.7	23.2	---
Base Number (BN)	mg KOH/g	ASTM D2896	10.5	7.6	7.3	---
Visc @ 100°C	cSt	ASTM D445	14	13.3	12.9	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0225412 **Received** : 27 Jun 2024
Lab Number : 06222193 **Tested** : 28 Jun 2024
Unique Number : 11100390 **Diagnosed** : 28 Jun 2024 - Don Baldrige
Test Package : CONST (Additional Tests: TBN)

JRE - MANASSAS PARK
 9107 OWENS DRIVE
 MANASSAS PARK, VA
 US 20111

Contact: DON VEST
 dvest@jamesriverequipment.com
 T: (703)631-8500
 F: (703)631-4715

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)