



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Area

(1203948)

Machine Id

926053-377

Component

Diesel Engine

Fluid

PETRO CANADA DURON SHP 15W40 (12 GAL)

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0125853</b>	GFL0118683	GFL0118711
Sample Date		Client Info		<b>24 Jun 2024</b>	05 Jun 2024	29 Apr 2024
Machine Age	hrs	Client Info		<b>27724</b>	26969	166406
Oil Age	hrs	Client Info		<b>200</b>	170	166406
Filter Age	hrs	Client Info		<b>200</b>	170	0
Oil Changed		Client Info		<b>Not Changd</b>	Changed	Not Changd
Filter Changed		Client Info		<b>Not Changd</b>	Changed	Not Changd
Sample Status				<b>NORMAL</b>	ABNORMAL	ABNORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>90	<b>14</b>	▲ 98	▲ 75
Chromium	ppm	ASTM D5185m	>20	<b>1</b>	6	5
Nickel	ppm	ASTM D5185m	>2	<b>&lt;1</b>	▲ 3	▲ 2
Titanium	ppm	ASTM D5185m	>2	<b>&lt;1</b>	<1	0
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>9</b>	▲ 45	▲ 40
Lead	ppm	ASTM D5185m	>40	<b>0</b>	<1	<1
Copper	ppm	ASTM D5185m	>330	<b>1</b>	7	4
Tin	ppm	ASTM D5185m	>15	<b>0</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	<b>5</b>	12	9
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	2	0
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>6	<b>0.2</b>	1.5	1.2
Nitration	Abs/cm	*ASTM D7624	>20	<b>5.0</b>	10.3	9.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>17.8</b>	22.2	21.5
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>8</b>	13	7
Boron	ppm	ASTM D5185m	0	<b>&lt;1</b>	0	0
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>58</b>	65	66
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	1	0
Magnesium	ppm	ASTM D5185m	1010	<b>1025</b>	979	1087
Calcium	ppm	ASTM D5185m	1070	<b>1087</b>	1104	1212
Phosphorus	ppm	ASTM D5185m	1150	<b>1165</b>	966	1150
Zinc	ppm	ASTM D5185m	1270	<b>1353</b>	1237	1427
Sulfur	ppm	ASTM D5185m	2060	<b>3790</b>	3108	3857
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>13.0</b>	16.2	15.7
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>9.6</b>	8.8	8.6
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.3</b>	14.5	14.5


**FT-IR (Direct Trend)**




**Base Number**




**Viscosity @ 100°C**




**Ferrous Alloys**




**Non-ferrous Metals**



**Viscosity @ 100°C**



**Base Number**



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0125853  
**Lab Number** : 06222213  
**Unique Number** : 11100410  
**Test Package** : FLEET

**Received** : 27 Jun 2024  
**Tested** : 28 Jun 2024  
**Diagnosed** : 28 Jun 2024 - Wes Davis

**GFL Environmental - 166 - Phenix City**  
 18 Old Brickyard Rd  
 Phenix City, AL  
 US 36869  
 Contact: DEAN PEACE JR  
 dean.peace@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: