



# VOLVO PENTA

## OIL ANALYSIS REPORT

|                 |        |
|-----------------|--------|
| WEAR            | NORMAL |
| CONTAMINATION   | NORMAL |
| FLUID CONDITION | NORMAL |

Area

**STEVE GANO**

Machine Id

**VOLVO PENTA 3940020499**

Component

**IPS**

Fluid

{not provided} (4 GAL)

### RECOMMENDATION

No corrective action is recommended at this time. Resample at the next service interval to monitor.

| Test           | UOM | Method      | Limit/Abn | Current     | History1 | History2 |
|----------------|-----|-------------|-----------|-------------|----------|----------|
| Sample Number  |     | Client Info |           | VPA061841   | ---      | ---      |
| Sample Date    |     | Client Info |           | 25 Jun 2024 | ---      | ---      |
| Machine Age    | hrs | Client Info |           | 267         | ---      | ---      |
| Oil Age        | hrs | Client Info |           | 0           | ---      | ---      |
| Filter Age     | hrs | Client Info |           | 0           | ---      | ---      |
| Oil Changed    |     | Client Info |           | Not Changd  | ---      | ---      |
| Filter Changed |     | Client Info |           | Not Changd  | ---      | ---      |
| Sample Status  |     |             |           | NORMAL      | ---      | ---      |

### WEAR

All component wear rates are normal.

|              |        |             |      |      |     |     |
|--------------|--------|-------------|------|------|-----|-----|
| PQ           |        | ASTM D8184  |      | 20   | --- | --- |
| Iron         | ppm    | ASTM D5185m | >275 | 8    | --- | --- |
| Chromium     | ppm    | ASTM D5185m | >4   | <1   | --- | --- |
| Nickel       | ppm    | ASTM D5185m | >4   | 0    | --- | --- |
| Titanium     | ppm    | ASTM D5185m | >3   | <1   | --- | --- |
| Silver       | ppm    | ASTM D5185m |      | 0    | --- | --- |
| Aluminum     | ppm    | ASTM D5185m | >10  | 3    | --- | --- |
| Lead         | ppm    | ASTM D5185m | >4   | 0    | --- | --- |
| Copper       | ppm    | ASTM D5185m | >30  | <1   | --- | --- |
| Tin          | ppm    | ASTM D5185m | >3   | 0    | --- | --- |
| Vanadium     | ppm    | ASTM D5185m |      | 0    | --- | --- |
| White Metal  | scalar | *Visual     | NONE | NONE | --- | --- |
| Yellow Metal | scalar | *Visual     | NONE | NONE | --- | --- |

### CONTAMINATION










There is no indication of any contamination in the oil.

|                  |        |             |       |       |     |     |
|------------------|--------|-------------|-------|-------|-----|-----|
| Silicon          | ppm    | ASTM D5185m | >35   | 15    | --- | --- |
| Potassium        | ppm    | ASTM D5185m | >20   | 1     | --- | --- |
| Water            |        | WC Method   | >0.2  | NEG   | --- | --- |
| Silt             | scalar | *Visual     | NONE  | NONE  | --- | --- |
| Debris           | scalar | *Visual     | NONE  | NONE  | --- | --- |
| Sand/Dirt        | scalar | *Visual     | NONE  | NONE  | --- | --- |
| Appearance       | scalar | *Visual     | NORML | NORML | --- | --- |
| Odor             | scalar | *Visual     | NORML | NORML | --- | --- |
| Emulsified Water | scalar | *Visual     | >0.2  | NEG   | --- | --- |

### FLUID CONDITION

The condition of the oil is acceptable for the time in service.

|             |     |             |  |       |     |     |
|-------------|-----|-------------|--|-------|-----|-----|
| Sodium      | ppm | ASTM D5185m |  | 0     | --- | --- |
| Boron       | ppm | ASTM D5185m |  | 318   | --- | --- |
| Barium      | ppm | ASTM D5185m |  | 0     | --- | --- |
| Molybdenum  | ppm | ASTM D5185m |  | <1    | --- | --- |
| Manganese   | ppm | ASTM D5185m |  | 0     | --- | --- |
| Magnesium   | ppm | ASTM D5185m |  | <1    | --- | --- |
| Calcium     | ppm | ASTM D5185m |  | 0     | --- | --- |
| Phosphorus  | ppm | ASTM D5185m |  | 1427  | --- | --- |
| Zinc        | ppm | ASTM D5185m |  | 4     | --- | --- |
| Sulfur      | ppm | ASTM D5185m |  | 26846 | --- | --- |
| Visc @ 40°C | cSt | ASTM D445   |  | 110   | --- | --- |



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : VPA061841 **Received** : 27 Jun 2024  
**Lab Number** : 06222584 **Tested** : 28 Jun 2024  
**Unique Number** : 11100781 **Diagnosed** : 28 Jun 2024 - Doug Bogart  
**Test Package** : MOB 1 ( Additional Tests: PQ )

**Mobile Marine Services Inc**  
 01032 Advance Rd South  
 EAST JORDAN, MI  
 US 49727  
 Contact: Duane Kujat  
 mobilemarine@twin-valley.net  
 T: Phone  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)