



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	ATTENTION



Machine Id
LIEBHERR A934C-HD-LI C-48 (S/N 045988-1007)
Component
Splitter Box
Fluid
CHEVRON MULTIGEAR EP5 80W90 (3 QTS)

RECOMMENDATION

The oil change at the time of sampling has been noted. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0920327	WC0794443	WC0692233
Sample Date		Client Info		24 Jun 2024	23 Jun 2023	29 Aug 2022
Machine Age	hrs	Client Info		26123	25091	23967
Oil Age	hrs	Client Info		2000	1124	929
Filter Age	hrs	Client Info		0	0	929
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Not Changed	Changed	Changed
Sample Status				ATTENTION	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	76	▲ 122	92
Chromium	ppm	ASTM D5185m	>5	1	2	1
Nickel	ppm	ASTM D5185m	>5	<1	<1	0
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m		0	0	<1
Aluminum	ppm	ASTM D5185m	>20	3	3	5
Lead	ppm	ASTM D5185m	>30	<1	<1	<1
Copper	ppm	ASTM D5185m	>20	1	1	<1
Tin	ppm	ASTM D5185m	>10	0	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	MODER
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION





There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>30	10	14	8
Potassium	ppm	ASTM D5185m	>20	5	4	6
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The oil viscosity is lower than normal. Confirm oil type.

Sodium	ppm	ASTM D5185m	>25	<1	0	0
Boron	ppm	ASTM D5185m		57	40	113
Barium	ppm	ASTM D5185m		0	0	2
Molybdenum	ppm	ASTM D5185m		1	0	2
Manganese	ppm	ASTM D5185m		<1	1	1
Magnesium	ppm	ASTM D5185m		10	12	7
Calcium	ppm	ASTM D5185m		879	126	296
Phosphorus	ppm	ASTM D5185m		658	486	833
Zinc	ppm	ASTM D5185m		435	172	224
Sulfur	ppm	ASTM D5185m		10820	12115	12932
Visc @ 40°C	cSt	ASTM D445		● 79.0	● 94.0	104



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0920327
Lab Number : 06222630
Unique Number : 11100827
Test Package : CONST
Received : 27 Jun 2024
Tested : 28 Jun 2024
Diagnosed : 29 Jun 2024 - Don Baldrige

FRANKLIN IRON & METAL CORP
 1939 EAST 1ST ST
 DAYTON, OH
 US 45403
 Contact: BILL PITTL JR
 parts@frankliniron.com
 T: (937)253-8184
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)