



LIEBHERR

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
LIEBHERR LH30M 1253-123497
Component
Front Right Wheel Hub
Fluid
SUPER S 80W90 LS (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LH0273455	LH0272905	LH0212312
Sample Date		Client Info		20 Jun 2024	11 Jan 2024	30 Dec 2021
Machine Age	hrs	Client Info		5603	4554	981
Oil Age	hrs	Client Info		500	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		N/A	None	None
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>450	43	56	72
Chromium	ppm	ASTM D5185m	>4	<1	<1	1
Nickel	ppm	ASTM D5185m	>2	<1	0	0
Titanium	ppm	ASTM D5185m		<1	0	<1
Silver	ppm	ASTM D5185m		<1	0	<1
Aluminum	ppm	ASTM D5185m	>15	3	2	0
Lead	ppm	ASTM D5185m	>4	0	0	<1
Copper	ppm	ASTM D5185m	>75	5	6	11
Tin	ppm	ASTM D5185m		0	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	LIGHT
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION





There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>60	3	3	5
Potassium	ppm	ASTM D5185m	>20	<1	1	0
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		2	<1	6
Boron	ppm	ASTM D5185m		2	4	73
Barium	ppm	ASTM D5185m		<1	4	0
Molybdenum	ppm	ASTM D5185m		<1	0	<1
Manganese	ppm	ASTM D5185m		<1	0	1
Magnesium	ppm	ASTM D5185m		2	<1	3
Calcium	ppm	ASTM D5185m		72	133	625
Phosphorus	ppm	ASTM D5185m		270	343	574
Zinc	ppm	ASTM D5185m		25	19	354
Sulfur	ppm	ASTM D5185m		18782	17832	18670
Visc @ 40°C	cSt	ASTM D445		125	120	103



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LH0273455 **Received** : 27 Jun 2024
Lab Number : 06222646 **Tested** : 28 Jun 2024
Unique Number : 11100843 **Diagnosed** : 28 Jun 2024 - Wes Davis
Test Package : CONST

SPARTAN RECYCLING
 3071 HOWARD ST
 SPARTANBURG, SC
 US 29303
 Contact: SERVICE MANAGER

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: