



|                 |               |
|-----------------|---------------|
| WEAR            | <b>NORMAL</b> |
| CONTAMINATION   | <b>NORMAL</b> |
| FLUID CONDITION | <b>NORMAL</b> |



Machine Id  
**212031**  
Component  
**Diesel Engine**  
Fluid  
**DIESEL ENGINE OIL SAE 40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

| Test           | UOM | Method      | Limit/Abn | Current            | History1    | History2    |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number  |     | Client Info |           | <b>GFL0115403</b>  | GFL0102990  | GFL0086369  |
| Sample Date    |     | Client Info |           | <b>27 Jun 2024</b> | 13 Apr 2024 | 30 Aug 2023 |
| Machine Age    | hrs | Client Info |           | <b>1336</b>        | 1188        | 774         |
| Oil Age        | hrs | Client Info |           | <b>0</b>           | 0           | 0           |
| Filter Age     | hrs | Client Info |           | <b>0</b>           | 0           | 0           |
| Oil Changed    |     | Client Info |           | <b>N/A</b>         | N/A         | N/A         |
| Filter Changed |     | Client Info |           | <b>N/A</b>         | N/A         | N/A         |
| Sample Status  |     |             |           | <b>NORMAL</b>      | NORMAL      | MARGINAL    |

**WEAR**

All component wear rates are normal.

|              |        |             |      |              |      |      |
|--------------|--------|-------------|------|--------------|------|------|
| Iron         | ppm    | ASTM D5185m | >80  | <b>23</b>    | 10   | 37   |
| Chromium     | ppm    | ASTM D5185m | >5   | <b>2</b>     | <1   | 4    |
| Nickel       | ppm    | ASTM D5185m | >2   | <b>1</b>     | 0    | <1   |
| Titanium     | ppm    | ASTM D5185m |      | <b>&lt;1</b> | 0    | 0    |
| Silver       | ppm    | ASTM D5185m | >3   | <b>&lt;1</b> | 0    | <1   |
| Aluminum     | ppm    | ASTM D5185m | >30  | <b>4</b>     | 2    | 2    |
| Lead         | ppm    | ASTM D5185m | >30  | <b>0</b>     | 0    | 0    |
| Copper       | ppm    | ASTM D5185m | >150 | <b>2</b>     | 3    | 7    |
| Tin          | ppm    | ASTM D5185m | >5   | <b>0</b>     | <1   | 0    |
| Vanadium     | ppm    | ASTM D5185m |      | <b>&lt;1</b> | 0    | 0    |
| White Metal  | scalar | *Visual     | NONE | <b>NONE</b>  | NONE | NONE |
| Yellow Metal | scalar | *Visual     | NONE | <b>NONE</b>  | NONE | NONE |

**CONTAMINATION**








There is no indication of any contamination in the oil.

|                  |          |             |       |                |       |       |
|------------------|----------|-------------|-------|----------------|-------|-------|
| Silicon          | ppm      | ASTM D5185m | >20   | <b>5</b>       | 5     | 6     |
| Potassium        | ppm      | ASTM D5185m | >20   | <b>5</b>       | 1     | 0     |
| Fuel             |          | WC Method   | >5    | <b>&lt;1.0</b> | <1.0  | ▲ 4.7 |
| Water            |          | WC Method   | >0.2  | <b>NEG</b>     | NEG   | NEG   |
| Glycol           |          | WC Method   |       | <b>NEG</b>     | NEG   | NEG   |
| Soot %           | %        | *ASTM D7844 | >3    | <b>0.4</b>     | 0.1   | 0.5   |
| Nitration        | Abs/cm   | *ASTM D7624 | >20   | <b>8.0</b>     | 5.5   | 10.4  |
| Sulfation        | Abs/.1mm | *ASTM D7415 | >30   | <b>20.3</b>    | 19.0  | 20.7  |
| Silt             | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Debris           | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Sand/Dirt        | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Appearance       | scalar   | *Visual     | NORML | <b>NORML</b>   | NORML | NORML |
| Odor             | scalar   | *Visual     | NORML | <b>NORML</b>   | NORML | NORML |
| Emulsified Water | scalar   | *Visual     | >0.2  | <b>NEG</b>     | NEG   | NEG   |

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

|                  |          |             |      |             |      |      |
|------------------|----------|-------------|------|-------------|------|------|
| Sodium           | ppm      | ASTM D5185m | >216 | <b>3</b>    | 1    | 2    |
| Boron            | ppm      | ASTM D5185m | 250  | <b>30</b>   | 54   | 0    |
| Barium           | ppm      | ASTM D5185m | 10   | <b>0</b>    | 0    | 0    |
| Molybdenum       | ppm      | ASTM D5185m | 100  | <b>61</b>   | 58   | 60   |
| Manganese        | ppm      | ASTM D5185m |      | <b>2</b>    | <1   | 2    |
| Magnesium        | ppm      | ASTM D5185m | 450  | <b>854</b>  | 789  | 806  |
| Calcium          | ppm      | ASTM D5185m | 3000 | <b>1390</b> | 1297 | 1279 |
| Phosphorus       | ppm      | ASTM D5185m | 1150 | <b>1065</b> | 1025 | 1018 |
| Zinc             | ppm      | ASTM D5185m | 1350 | <b>1319</b> | 1206 | 1251 |
| Sulfur           | ppm      | ASTM D5185m | 4250 | <b>3834</b> | 3630 | 3524 |
| Oxidation        | Abs/.1mm | *ASTM D7414 | >25  | <b>15.5</b> | 14.3 | 16.9 |
| Base Number (BN) | mg KOH/g | ASTM D2896  | 8.5  | <b>8.5</b>  | 8.7  | 6.6  |
| Visc @ 100°C     | cSt      | ASTM D445   | 14.4 | <b>13.1</b> | 14.2 | 11.7 |



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0115403  
**Lab Number** : 06223040  
**Unique Number** : 11101237  
**Test Package** : FLEET

**Received** : 27 Jun 2024  
**Tested** : 28 Jun 2024  
**Diagnosed** : 30 Jun 2024 - Don Baldrige

**GFL Environmental - 816 - WCA of South Arkansas**  
 3083 Smackover Hwy  
 El Dorado, AR  
 US 71730  
 Contact: Mike Howell  
 mike.howell@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: