



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
724033-3070
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0103534	GFL0103537	GFL0085335
Sample Date		Client Info		24 Jun 2024	13 Feb 2024	28 Aug 2023
Machine Age	hrs	Client Info		7960	0	0
Oil Age	hrs	Client Info		0	159	542
Filter Age	hrs	Client Info		0	159	542
Oil Changed		Client Info		Not Changd	Not Changd	N/A
Filter Changed		Client Info		Not Changd	Not Changd	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	72	41	75
Chromium	ppm	ASTM D5185m	>20	4	2	4
Nickel	ppm	ASTM D5185m	>4	1	<1	<1
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>3	<1	0	<1
Aluminum	ppm	ASTM D5185m	>20	20	9	5
Lead	ppm	ASTM D5185m	>40	10	4	15
Copper	ppm	ASTM D5185m	>330	7	3	21
Tin	ppm	ASTM D5185m	>15	<1	1	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	5	4	12
Potassium	ppm	ASTM D5185m	>20	10	8	6
Fuel		WC Method	>2.0	<1.0	1.8	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	1.2	0.8	2.5
Nitration	Abs/cm	*ASTM D7624	>20	9.4	7.4	12.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.2	19.9	27.9
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		11	8	13
Boron	ppm	ASTM D5185m	0	9	4	15
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	59	54	38
Manganese	ppm	ASTM D5185m	0	2	<1	3
Magnesium	ppm	ASTM D5185m	1010	984	832	633
Calcium	ppm	ASTM D5185m	1070	1213	990	1517
Phosphorus	ppm	ASTM D5185m	1150	1072	960	785
Zinc	ppm	ASTM D5185m	1270	1325	1132	996
Sulfur	ppm	ASTM D5185m	2060	3724	2781	2912
Oxidation	Abs/.1mm	*ASTM D7414	>25	17.8	15.2	24.1
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	9.3	9.4	10.1
Visc @ 100°C	cSt	ASTM D445	15.4	12.6	12.0	13.1



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0103534 **Received** : 27 Jun 2024
Lab Number : 06223055 **Tested** : 28 Jun 2024
Unique Number : 11101252 **Diagnosed** : 30 Jun 2024 - Don Baldrige
Test Package : FLEET

GFL Environmental - 958A - Chillicothe Wigan
 19908 N. State Rd 29
 Chillicothe, IL
 US 61523
 Contact: Bryan Link
 blink@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: