



# VOLVO

## OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Area

[SW-35455-2]

Machine Id

5394 VOLVO L150H 5394

Component

Diesel Engine

Fluid

VOLVO ULTRA DIESEL ENGINE OIL 15W40 VDS-3 (14 LTR)

### RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VCP247819D	DJJ0009062	DJJ0009395
Sample Date		Client Info		20 Jun 2024	17 Apr 2024	28 Feb 2024
Machine Age	hrs	Client Info		15960	15562	15223
Oil Age	hrs	Client Info		400	300	350
Filter Age	hrs	Client Info		0	300	350
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

### WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	3	1	2
Chromium	ppm	ASTM D5185m	>10	<1	0	<1
Nickel	ppm	ASTM D5185m	>10	<1	0	0
Titanium	ppm	ASTM D5185m		1	<1	<1
Silver	ppm	ASTM D5185m	>2	<1	0	0
Aluminum	ppm	ASTM D5185m	>10	2	<1	2
Lead	ppm	ASTM D5185m	>20	<1	<1	0
Copper	ppm	ASTM D5185m	>15	1	0	<1
Tin	ppm	ASTM D5185m	>10	<1	0	0
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

### CONTAMINATION












There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	4	2	3
Potassium	ppm	ASTM D5185m	>20	2	<1	1
Fuel		WC Method	>6.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.1	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	6.1	5.9	6.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	16.6	16.1	16.9
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

### FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<1	<1	<1
Boron	ppm	ASTM D5185m	2.5	15	22	23
Barium	ppm	ASTM D5185m	0.0	1	0	0
Molybdenum	ppm	ASTM D5185m	0.7	19	22	57
Manganese	ppm	ASTM D5185m	0.0	<1	0	0
Magnesium	ppm	ASTM D5185m	256	207	283	744
Calcium	ppm	ASTM D5185m	2057	2027	1989	1181
Phosphorus	ppm	ASTM D5185m	935	890	930	1060
Zinc	ppm	ASTM D5185m	1223	1048	1095	1137
Sulfur	ppm	ASTM D5185m	4079	3394	4032	3424
Oxidation	Abs/.1mm	*ASTM D7414	>25	9.4	9.9	12.4
Base Number (BN)	mg KOH/g	ASTM D2896	10	6.8	7.0	8.1
Visc @ 100°C	cSt	ASTM D445	15.0	12.9	13.0	12.9



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : VCP247819D  
**Lab Number** : 06223087  
**Unique Number** : 11101284  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**Received** : 28 Jun 2024  
**Tested** : 28 Jun 2024  
**Diagnosed** : 28 Jun 2024 - Wes Davis

**WESTERN METALS RECYCLING - SALT LAKE CITY**  
 4221 WEST 700 SOUTH  
 SALT LAKE CITY, UT  
 US 84104  
 Contact: TIMOTHY SHEFFIELD  
 timothy.sheffield@wmrecycling.com  
 T: (801)373-4225  
 F: (801)975-9590

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)