



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
Store 4 - Fairmont [RO# 152502]
 Machine Id
JOHN DEERE 35G 1FF035GXPGK277166
 Component
Diesel Engine
 Fluid
DIESEL ENGINE OIL SAE 15W40 (2 GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LEC0048323	LEC0016371	LECP192026
Sample Date		Client Info		25 Jun 2024	29 Oct 2020	06 Mar 2019
Machine Age	hrs	Client Info		1983	997	500
Oil Age	hrs	Client Info		986	497	500
Filter Age	hrs	Client Info		986	497	500
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

Metal levels are typical for a new component breaking in.

Iron	ppm	ASTM D5185m	>51	18	29	71
Chromium	ppm	ASTM D5185m	>11	<1	<1	<1
Nickel	ppm	ASTM D5185m	>5	0	0	<1
Titanium	ppm	ASTM D5185m		<1	<1	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>31	2	0	5
Lead	ppm	ASTM D5185m	>26	0	2	4
Copper	ppm	ASTM D5185m	>26	5	4	13
Tin	ppm	ASTM D5185m	>4	0	<1	0
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>120	9	16	55
Potassium	ppm	ASTM D5185m	>20	7	<1	3
Fuel		WC Method	>2.1	<1.0	<1.0	<1.0
Water		WC Method	>0.21	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.6	0.6	0.4
Nitration	Abs/cm	*ASTM D7624	>20	10.0	11	9.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.9	24.5	17.7
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.21	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>158	3	<1	16
Boron	ppm	ASTM D5185m	250	153	206	36
Barium	ppm	ASTM D5185m	10	0	<1	5
Molybdenum	ppm	ASTM D5185m	100	18	244	97
Manganese	ppm	ASTM D5185m		<1	<1	5
Magnesium	ppm	ASTM D5185m	450	72	701	14
Calcium	ppm	ASTM D5185m	3000	2555	1786	4167
Phosphorus	ppm	ASTM D5185m	1150	1122	972	992
Zinc	ppm	ASTM D5185m	1350	1365	1101	1247
Sulfur	ppm	ASTM D5185m	4250	4399	2929	5780
Oxidation	Abs/.1mm	*ASTM D7414	>25	20.2	20.6	11.8
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	6.7	9.7	12.6
Visc @ 100°C	cSt	ASTM D445	14.4	13.7	13.1	9.48


FT-IR (Direct Trend)




Ferrous Alloys




Base Number




Non-ferrous Metals




Viscosity @ 100°C



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LEC0048323 **Received** : 28 Jun 2024
Lab Number : 06223245 **Tested** : 28 Jun 2024
Unique Number : 11101442 **Diagnosed** : 28 Jun 2024 - Wes Davis
Test Package : CONST (Additional Tests: TBN)

LESLIE EQUIPMENT COMPANY
 105 TENNIS CENTER DR.
 MARIETTA, OH
 US 45750-9765
 Contact: LEANNE KENDALL
 KendalLeanne@lec1.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: (740)373-5570